

**DEMOCRATIC SOCIALIST REPUBLIC OF
SRI LANKA**



UNIVERSITY OF JAFFNA, SRI LANKA

**SUPPLY OF MECHANICAL AND CIVIL ENGINEERING
EQUIPMENT TO THE FACULTY OF ENGINEERING
UNIVERSITY OF JAFFNA**

UJ/F/PO/T/03/2016

Package 01

BIDDING DOCUMENT

Bid Opening on	23.06.2016
Bid Validity up to	23.09.2016


M. G. L. Maveekumbura
Senior Assistant Bursar (Supplies)
University of Jaffna
Jaffna

Client

University of Jaffna,
P. O. Box 57, Thirunelvely,
Jaffna,
Sri Lanka.

CONTENTS

Content	Page Nos.
Section I: Instructions to Bidders (ITB)	03-14
Section VI: Conditions of Contract (CC)	15-26
Section VIII: Contract Forms	27-30
Section II: Bidding Data Sheet (BDS)	31-33
Section III: Evaluation and Qualification Criteria	34-35
Section IV: Bidding Forms	36-41
Price Schedule	38-39
Section V Schedule of Requirements	42-94
List of goods and delivery schedule	42-43
Technical specification	44-67
Bidder's response	68-94
Section VII: Contract Data	95
Invitation for Bid	96-98

Section I.

Instructions to Bidders (ITB)

ITB shall be read in conjunction with the Section II, Bidding Data Sheet (BDS), which shall take precedence over ITB.

General	
1. Scope of Bid	<p>1.1 The Purchaser indicated in the Bidding Data Sheet (BDS), issues these Bidding Documents for the supply of Goods and Related Services incidental thereto as specified in Section V, Schedule of Requirements. The name and identification number of this procurement are specified in the BDS. The name, identification, and number of lots (individual contracts), if any, are provided in the BDS.</p> <p>1.2 Throughout these Bidding Documents:</p> <p>(a) the term “in writing” means communicated in written form by mail (other than electronic mail) or hand delivered with proof of receipt;</p> <p>(b) if the context so requires, “singular” means “plural” and vice versa; and</p> <p>(c) “Day” means calendar day.</p>
2. Source of Funds	<p>2.1 Payments under this contract will be financed by the source specified in the BDS.</p>
3. Ethics, Fraud and Corruption	<p>3.1 The attention of the bidders is drawn to the following guidelines of the Procurement Guidelines published by National Procurement Agency:</p> <ul style="list-style-type: none">▪ Parties associated with Procurement Actions, namely, suppliers/contractors and officials shall ensure that they maintain strict confidentiality throughout the process;▪ Officials shall refrain from receiving any personal gain from any Procurement Action. No gifts or inducement shall be accepted. Suppliers/contractors are liable to be disqualified from the bidding process if found offering any gift or inducement which may have an effect of influencing a decision or impairing the objectivity of an official. <p>3.2 The Purchaser requires the bidders, suppliers, contractors, and consultants to observe the highest standard of ethics during the procurement and execution of such contracts. In pursuit of this policy:</p> <p>(a) “corrupt practice” means the offering, giving, receiving, or soliciting, directly or indirectly, of anything of value to influence the action of a public official in the procurement process or in contract execution;</p> <p>(b) “fraudulent practice” means a misrepresentation or omission of facts in order</p>

	<p>to influence a procurement process or the execution of a contract;</p> <p>(c) “collusive practice” means a scheme or arrangement between two or more bidders, with or without the knowledge of the Purchaser to establish bid prices at artificial, noncompetitive levels; and</p> <p>(d) “Coercive practice” means harming or threatening to harm, directly or indirectly, persons or their property to influence their participation in the procurement process or affect the execution of a contract.</p> <p>3.3 If the Purchaser found any unethical practices as stipulated under ITB Clause 3.2, the Purchaser will reject a bid, if it is found that a Bidder directly or through an agent, engaged in corrupt, fraudulent, collusive or coercive practices in competing for the Contract in question.</p>
<p>4. Eligible Bidders</p>	<p>4.1 All bidders shall possess legal rights to supply the Goods under this contract.</p> <p>4.2 A Bidder shall not have a conflict of interest. All bidders found to have conflict of interest shall be disqualified. Bidders may be considered to have a conflict of interest with one or more parties in this bidding process, if they:</p> <p>(a) are or have been associated in the past, with a firm or any of its affiliates which have been engaged by the purchaser to provide consulting services for the preparation of the design, specifications, and other documents to be used for the procurement of the goods to be purchased under these Bidding Documents ; or</p> <p>(b) Submit more than one bid in this bidding process. However, this does not limit the participation of subcontractors in more than one bid.</p> <p>4.3 A Bidder that is under a declaration of ineligibility by the National Procurement Agency (NPA), at the date of submission of bids or at the date of contract award, shall be disqualified. The list of debarred firms is available at the website of NPA, www.npa.gov.lk .</p> <p>4.4 Foreign Bidder may submit a bid only if so stated in the BDS.</p>
<p>5. Eligible Goods and Related Services</p>	<p>5.1 All goods supplied under this contract shall be complied with applicable standards stipulated by the Sri Lanka Standards Institute (SLSI). In the absence of such standards, the Goods supplied shall be complied tother internationally accepted standards.</p>
<p>Contents of Bidding Documents</p>	
<p>6. Sections of Bidding Documents</p>	<p>6.1 The Bidding Documents consist of 2 Volumes, which include all the sections indicated below, and should be read in conjunction with any addendum issued in accordance with ITB Clause 8.</p> <p>Volume 1</p> <ul style="list-style-type: none"> • Section I. Instructions to Bidders (ITB) • Section VI. Conditions of Contract (CC) • Section VIII. Contract Forms

	<p>Volume 2</p> <ul style="list-style-type: none"> • Section II. Bidding Data Sheet (BDS) • Section III. Evaluation and Qualification Criteria • Section IV. Bidding Forms • Section V. Schedule of Requirements • Section VII. Contract Data • Invitation For Bid <p>6.2 The Bidder is expected to examine all instructions, forms, terms, and specifications in the Bidding Documents. Failure to furnish all information or documentation required by the Bidding Documents may result in the rejection of the bid.</p>
7. Clarification of Bidding Documents	<p>7.1 A prospective Bidder requiring any clarification of the Bidding Documents including the restrictiveness of specifications shall contact the Purchaser in writing at the Purchaser's address specified in the BDS. The Purchaser will respond in writing to any request for clarification, provided that such request is received no later than ten (10) days prior to the deadline for submission of bids. The purchaser shall forward copies of its response to all those who have purchased the Bidding Documents, including a description of the inquiry but without identifying its source. Should the Purchaser deem it necessary to amend the Bidding Documents as a result of a clarification, it shall do so following the procedure under ITB Clause 8.</p>
8. Amendment of Bidding Documents	<p>8.1 At any time prior to the deadline for submission of bids, the Purchaser may amend the Bidding Documents by issuing addendum.</p> <p>8.2 Any addendum issued shall be part of the Bidding Documents and shall be communicated in writing to all who have purchased the Bidding Documents.</p> <p>8.3 To give prospective Bidders reasonable time in which to take an addendum into account in preparing their bids, the purchaser may, at its discretion, extend the deadline for the submission of bids, pursuant to ITB Sub-Clause 23.2</p>
Preparation of Bids	
9. Cost of Bidding	<p>9.1 The Bidder shall bear all costs associated with the preparation and submission of its bid, and the Purchaser shall not be responsible or liable for those costs, regardless of the conduct or outcome of the bidding process.</p>
10. Language of Bid	<p>10.1 The Bid, as well as all correspondence and documents relating to the Bid (including supporting documents and printed literature) exchanged by the Bidder and the Purchaser, shall be written in English language.</p>
11. Documents Comprising the Bid	<p>11.1 The Bid shall comprise the following:</p> <p>(a) Bid Submission Form and the applicable Price Schedules, in accordance with ITB Clauses 12, 14, and 15;</p> <p>(b) Bid Security or Bid-Securing Declaration, in accordance with ITB Clause 20;</p>

	<p>(c) documentary evidence in accordance with ITB Clauses 18 and 29, that the Goods and Related Services conform to the Bidding Documents;</p> <p>(d) documentary evidence in accordance with ITB Clause 18 establishing the Bidder's qualifications to perform the contract if its bid is accepted; and</p> <p>(e) Any other document required in the BDS.</p>
12. Bid Submission Form and Price Schedules	12.1 The Bidder shall submit the Bid Submission Form using the form furnished in Section IV, Bidding Forms. This form must be completed without any alterations to its format, and no substitutes shall be accepted. All blank spaces shall be filled in with the information requested.
13. Alternative Bids	13.1 Alternative bids shall not be considered.
14. Bid Prices and Discounts	<p>14.1 The Bidder shall indicate on the Price Schedule the unit prices and total bid prices of the goods it proposes to supply under the Contract.</p> <p>14.2 Any discount offered against any single item in the price schedule shall be included in the unit price of the item. However, a Bidder wishes to offer discount as a lot the bidder may do so by indicating such amounts appropriately.</p> <p>14.3 If so indicated in ITB Sub-Clause 1.1, bids are being invited for individual contracts (lots) or for any combination of contracts. Unless otherwise indicated in the BDS, prices quoted shall correspond to 100 % of the items specified for each lot and to 100% of the quantities specified for each item of a lot. Bidders wishing to offer any price reduction (discount) for the award of more than one Contract shall specify the applicable price reduction separately.</p> <p>14.4 (i) Prices indicated on the Price Schedule shall include all duties and sales and other taxes already paid or payable by the Supplier:</p> <p>(a) on components and raw material used in the manufacture or assembly of goods quoted; or</p> <p>(b) on the previously imported goods of foreign origin</p> <p>(ii) However, VAT shall not be included in the price but shall be indicated separately;</p> <p>(iii) the price for inland transportation, insurance and other related services to deliver the goods to their final destination;</p> <p>(iv) the price of other incidental services</p> <p>14.5 The Prices quoted by the Bidder shall be fixed during the Bidder's performance of the Contract and not subject to variation on any account. A bid submitted with an adjustable price quotation will be treated as non-responsive and rejected, pursuant to ITB Clause 31.</p> <p>14.6 All lots, if any and items must be listed and priced separately in the Price Schedules. If a Price Schedule shows items listed but not priced, their prices shall be assumed to be included in the prices of other items.</p>

15. Currencies of Bid	15.1 Unless otherwise stated in Bidding Data Sheet, the Bidder shall quote in Sri Lankan Rupees and payment shall be payable only in Sri Lanka Rupees.
16. Documents Establishing the Eligibility of the Bidder	16.1 To establish their eligibility in accordance with ITB Clause 4, Bidders shall complete the Bid Submission Form, included in Section IV, Bidding Forms.
17. Documents Establishing the Conformity of the Goods and Related Services	<p>17.1 To establish the conformity of the Goods and Related Services to the Bidding Documents, the Bidder shall furnish as part of its Bid the documentary evidence that the Goods conform to the technical specifications and standards specified in Section V, Schedule of Requirements.</p> <p>17.2 The documentary evidence may be in the form of literature, drawings or data, and shall consist of a detailed item by item description (given in Section V, Technical Specifications) of the essential technical and performance characteristics of the Goods and Related Services, demonstrating substantial responsiveness of the Goods and Related Services to the technical specification, and if applicable, a statement of deviations and exceptions to the provisions of the Schedule of Requirements.</p> <p>17.3 The Bidder shall also furnish a list giving full particulars, including quantities, available sources and current prices of spare parts, special tools, etc., necessary for the proper and continuing functioning of the Goods during the period if specified in the BDS following commencement of the use of the goods by the Purchaser.</p>
18. Documents Establishing the Qualifications of the Bidder	<p>18.1 The documentary evidence of the Bidder's qualifications to perform the contract if its bid is accepted shall establish to the Purchaser's satisfaction:</p> <p>(a) A Bidder that does not manufacture or produce the Goods it offers to supply shall submit the Manufacturer's Authorization using the form included in Section IV, Bidding Forms to demonstrate that it has been duly authorized by the manufacturer or producer of the Goods to supply these Goods;</p> <p>(b) that, if required in the BDS, in case of a Bidder not doing business within Sri Lanka, the Bidder is or will be (if awarded the contract) represented by an Agent in Sri Lanka equipped and able to carry out the Supplier's maintenance, repair and spare parts stocking obligations prescribed in the Conditions of Contract and/or Technical Specifications; and</p> <p>(c) That the Bidder meets each of the qualification criteria specified in Section III, Evaluation and Qualification Criteria.</p>
19. Period of Validity of Bids	<p>19.1 Bids shall remain valid until the date specified in the BDS. A bid valid for a shorter date shall be rejected by the Purchaser as non-responsive.</p> <p>19.2 In exceptional circumstances, prior to the expiration of the bid validity date, the Purchaser may request bidders to extend the period of validity of their bids. The request and the responses shall be made in writing. If a Bid Security is requested in accordance with ITB Clause 20, it shall also be extended for a corresponding period. A Bidder may refuse the request without forfeiting its Bid Security. A Bidder granting the request shall not be required or permitted to modify its bid.</p>

<p>20. Bid Security</p>	<p>20.1 The Bidder shall furnish as part of its bid, a Bid Security as specified in the BDS.</p> <p>20.2 The Bid Security shall be in the amount specified in the BDS and denominated in Sri Lanka Rupees, and shall:</p> <ul style="list-style-type: none"> (a) at the bidder’s option, be in the form of either a bank draft, a letter of credit, or a bank guarantee from a banking institution; (b) be issued by a institution acceptable to Purchaser. The acceptable institutes are published in the NPA website, www.npa.gov.lk. (c) be substantially in accordance with the form included in Section IV, Bidding Forms; (d) be payable promptly upon written demand by the Purchaser in case the conditions listed in ITB Clause 20.5 are invoked; (e) be submitted in its original form; copies will not be accepted; (f) Remain valid for the period specified in the BDS. <p>20.3 Any bid not accompanied by a substantially responsive Bid Security in accordance with ITB Sub-Clause 20.1 and 20.2, may be rejected by the Purchaser as non-responsive.</p> <p>20.4 The Bid Security of unsuccessful Bidders shall be returned as promptly as possible upon the successful Bidder’s furnishing of the Performance Security pursuant to ITB Clause 43.</p> <p>20.5 The Bid Security may be forfeited:</p> <ul style="list-style-type: none"> (a) if a Bidder withdraws its bid during the period of bid validity specified by the Bidder on the Bid Submission Form, except as provided in ITB Sub- Clause 19.2; or (b) if a Bidder does not agreeing to correction of arithmetical errors in pursuant to ITB Sub-Clause 30.3 (c) if the successful Bidder fails to: <ul style="list-style-type: none"> (i) sign the Contract in accordance with ITB Clause 42; (ii) Furnish a Performance Security in accordance with ITB Clause 43.
<p>21. Format and Signing of Bid</p>	<p>21.1 The Bidder shall prepare one original of the documents comprising the bid as described in ITB Clause 11 and clearly mark it as “ORIGINAL.” In addition, the Bidder shall submit a copy of the bid and clearly mark it as“COPY.” In the event of any discrepancy between the original and the copy, the original shall prevail.</p>

	<p>21.2 The original and the Copy of the bid shall be typed or written in indelible ink and shall be signed by a person duly authorized to sign on behalf of the Bidder.</p> <p>21.3 Any interlineations, erasures, or overwriting shall be valid only if they are signed or initialed by the person signing the Bid.</p>
<p>Submission and Opening of Bids</p>	
<p>22. Submission, Sealing and Marking of Bids</p>	<p>22.1 Bidders may always submit their bids by mail or by hand.</p> <p>(a) Bidders submitting bids by mail or by hand, shall enclose the original and the copy of the Bid in separate sealed envelopes, duly marking the envelopes as “ORIGINAL” and “COPY.” These envelopes containing the original and the copy shall then be enclosed in one single envelope.</p> <p>22.2 The inner and outer envelopes shall:</p> <p>(a) Bear the name and address of the Bidder;</p> <p>(b) be addressed to the Purchaser in accordance with ITB Sub-Clause 23.1;</p> <p>(c) bear the specific identification of this bidding process as indicated in the BDS; and</p> <p>(d) Bear a warning not to open before the time and date for bid opening, in accordance with ITB Sub-Clause 261. If all envelopes are not sealed and marked as required, the Purchaser will assume no responsibility for the misplacement or premature opening of the bid.</p>
<p>23. Deadline for Submission of Bids</p>	<p>23.1 Bids must be received by the Purchaser at the address and no later than the date and time specified in the BDS.</p> <p>23.2 The Purchaser may, at its discretion, extend the deadline for the submission of bids by amending the Bidding Documents in accordance with ITB Clause 8, in which case all rights and obligations of the Purchaser and Bidders previously subject to the deadline shall thereafter be subject to the deadline as extended.</p>
<p>24. Late Bids</p>	<p>24.1 The Purchaser shall not consider any bid that arrives after the deadline for submission of bids, in accordance with ITB Clause 23. Any bid received by the Purchaser after the deadline for submission of bids shall be declared late, rejected, and returned unopened to the Bidder.</p>
<p>25. Withdrawal, and Modification of Bids</p>	<p>25.1 A Bidder may withdraw, or modify its Bid after it has been submitted by sending a written notice in accordance with ITB Clause 22, duly signed by an authorized representative, and shall include a copy of the authorization in accordance with ITB Sub-Clause 21.2, (except that no copies of the withdrawal notice are required). The correspondingsubstitution or modification of the bid must accompany the respective written notice. All notices must be:</p> <p>(a) submitted in accordance with ITB Clauses 21 and 22 (except that withdrawal notices do not require copies), and in addition, the respective envelopes shall be clearly marked “WITHDRAWAL,” or “MODIFICATION;” and</p>

	<p>(b) Received by the Purchaser prior to the deadline prescribed for submission of bids, in accordance with ITB Clause 23.</p> <p>25.2 Bids requested to be withdrawn in accordance with ITB Sub-Clause 25.1 shall be returned to the Bidders only upon notification of contract award to the successful bidder in accordance with sub clause 41.1.</p> <p>25.3 No bid may be withdrawn, substituted, or modified in the interval between the deadline for submission of bids and the expiration of the period of bid validity specified by the Bidder on the Bid Submission Form or any extension thereof.</p>
<p>26. Bid Opening</p>	<p>26.1 The Purchaser shall conduct the bid opening in public at the address, date and time specified in the BDS.</p> <p>26.2 First, envelopes marked “WITHDRAWAL” shall be opened and read out and the envelope with the corresponding bid may be opened at the discretion of the Purchaser. No bid withdrawal shall be permitted unless the corresponding withdrawal notice contains a valid authorization to request the withdrawal and is read out at bid opening. Envelopes marked “MODIFICATION” shall be opened and read out with the corresponding Bid. No Bid modification shall be permitted unless the corresponding modification notice contains a valid authorization to request the modification and is read out at Bid opening. Only envelopes that are opened and read out at Bid opening shall be considered further.</p> <p>26.3 All other envelopes shall be opened one at a time, reading out: the name of the Bidder and whether there is a modification; the Bid Prices, including any discounts and alternative offers; the presence of a Bid Security or Bid- Securing Declaration, if required; and any other details as the Purchaser may consider appropriate. Only discounts and alternative offers read out at Bid opening shall be considered for evaluation. No Bid shall be rejected at Bid opening except for late bids, in accordance with ITB Sub Clause 24.1.</p> <p>26.4 The Purchaser shall prepare a record of the Bid opening that shall include, as a minimum: the name of the Bidder and whether there is a withdrawal, or modification; the Bid Price, per lot if applicable, including any discounts, and the presence or absence of a Bid Security. The bids that were opened shall be resealed in separate envelopes, promptly after the bid opening. The Bidders’ representatives who are present shall be requested to sign the attendance sheet. A copy of the record shall be distributed to all Bidders who submitted bids in time.</p>
<p>Evaluation and Comparison of Bids</p>	
<p>27. Confidentiality</p>	<p>27.1 Information relating to the examination, evaluation, comparison, and post-qualification (if applicable) of bids, and recommendation of contract award, shall not be disclosed to bidders or any other persons not officially concerned with such process until publication of the Contract Award.</p> <p>27.2 Any effort by a Bidder to influence the Purchaser in the examination, evaluation, comparison, and post-qualification of the bids or contract award decisions may result in the rejection of its Bid.</p>

	<p>27.3 Notwithstanding ITB Sub-Clause 27.2, if any Bidder wishes to contact the Purchaser on any matter related to the bidding process, from the time of bid opening to the time of Contract Award, it should do so in writing.</p>
28. Clarification of Bids	<p>28.1 To assist in the examination, evaluation, comparison and post-qualification of the bids, the Purchaser may, at its discretion, request any Bidder for a clarification of its Bid. Any clarification submitted by a Bidder in respect to its Bid and that is not in response to a request by the Purchaser shall not be considered for purpose of evaluation. The Purchaser's request for clarification and the response shall be in writing. No change in the prices or substance of the Bid shall be sought, offered, or permitted, except to confirm the correction of arithmetic errors discovered by the Purchaser in the Evaluation of the bids, in accordance with ITB Clause 30.</p>
29. Responsiveness of Bids	<p>29.1 The Purchaser's determination of a bid's responsiveness is to be based on the contents of the bid itself.</p> <p>29.2 A substantially responsive Bid is one that conforms to all the terms, conditions, and specifications of the Bidding Documents without material deviation, reservation, or omission. A material deviation, reservation, or omission is one that:</p> <p>(a) affects in any substantial way the scope, quality, or performance of the Goods and Related Services specified in the Contract; or</p> <p>(b) limits in any substantial way, inconsistent with the Bidding Documents, the Purchaser's rights or the Bidder's obligations under the Contract; or</p> <p>(c) If rectified would unfairly affect the competitive position of other bidders presenting substantially responsive bids.</p> <p>29.3 If a bid is not substantially responsive to the Bidding Documents, it shall be rejected by the Purchaser and may not subsequently be made responsive by the Bidder by correction of the material deviation, reservation, or omission.</p>
30. Nonconformities, Errors and Omissions	<p>30.1 Provided that a Bid is substantially responsive, the Purchaser may waive any non-conformities or omissions in the Bid that do not constitute a material deviation.</p> <p>30.2 Provided that a bid is substantially responsive, the Purchaser may request that the Bidder submit the necessary information or documentation, within a reasonable period of time, to rectify nonmaterial nonconformities or omissions in the bid related to documentation requirements. Such omission shall not be related to any aspect of the price of the Bid. Failure of the Bidder to comply with the request may result in the rejection of its Bid.</p> <p>30.3 Provided that the Bid is substantially responsive, the Purchaser shall correct arithmetical errors on the following basis:</p> <p>(a) if there is a discrepancy between the unit price and the line item total that is obtained by multiplying the unit price by the quantity, the unit price shall prevail and the line item total shall be corrected, unless in the opinion of the Purchaser there is an obvious misplacement of the decimal point in the unit price, in which case the line item total as quoted shall govern and the unit price shall be corrected;</p>

	<p>(b) if there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and</p> <p>(c) If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (a) and (b) above.</p> <p>30.4 If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid- Securing Declaration shall be executed.</p>
31. Preliminary Examination of Bids	<p>31.1 The Purchaser shall examine the bids to confirm that all documents and technical documentation requested in ITB Clause 11 have been provided, and to determine the completeness of each document submitted.</p> <p>31.2 The Purchaser shall confirm that the following documents and information have been provided in the Bid. If any of these documents or information is missing, the Bid shall be rejected.</p> <p>(a) Bid Submission Form, in accordance with ITB Sub- Clause 12.1;</p> <p>(b) Price Schedules, in accordance with ITB Sub-Clause 12;</p> <p>(c) Bid Security, in accordance with ITB Clause 20.</p>
32. Examination of Terms and Conditions; Technical Evaluation	<p>32.1 The Purchaser shall examine the Bid to confirm that all terms and conditions specified in the CC and the Contract Data have been accepted by the Bidder without any material deviation or reservation.</p> <p>32.2 The Purchaser shall evaluate the technical aspects of the Bid submitted in accordance with ITB Clause 17, to confirm that all requirements specified in Section V, Schedule of Requirements of the Bidding Documents have been met without any material deviation or reservation.</p> <p>32.3 If, after the examination of the terms and conditions and the technical evaluation, the Purchaser determines that the Bid is not substantially responsive in accordance with ITB Clause 29, the Purchaser shall reject the Bid.</p>
33. Conversion to Single Currency	<p>34.1 If the bidders are allowed to quote in foreign currencies in accordance with sub clause 15.1, for evaluation and comparison purposes, the Purchaser shall convert all bid prices expressed in foreign currencies in to Sri Lankan Rupees using the selling rates prevailed 28 days prior to closing of bids as published by the Central Bank of Sri Lanka. If this date falls on a public holiday the earliest working day prior to the date shall be applicable.</p>
34. Domestic Preference	<p>34.1 Domestic preference shall be a factor in bid evaluation only if stated in the BDS. If domestic preference shall be a bid evaluation factor, the methodology for calculating the margin of preference and the criteria for its application shall be as specified in Section III, Evaluation and Qualification Criteria.</p>
35. Evaluation of Bids	<p>35.1 The Purchaser shall evaluate each bid that has been determined, up to this stage of the evaluation, to be substantially responsive.</p> <p>35.2 To evaluate a Bid, the Purchaser shall only use all the factors, methodologies and criteria defined in this ITB Clause 35.</p>

	<p>35.3 To evaluate a Bid, the Purchaser shall consider the following:</p> <p>(a) the Bid Price as quoted in accordance with clause 14;</p> <p>(b) price adjustment for correction of arithmetic errors in accordance with ITB Sub-Clause 30.3;</p> <p>(c) price adjustment due to discounts offered in accordance with ITB Sub-Clause 14.2; and 14.3</p> <p>(d) adjustments due to the application of the evaluation criteria specified in the BDS from amongst those set out in Section III, Evaluation and Qualification Criteria;</p> <p>(e) Adjustments due to the application of a domestic preference, in accordance with ITB Clause 34 if applicable.</p> <p>35.4 The Purchaser’s evaluation of a bid may require the consideration of other factors, in addition to the factors stated in ITB Sub-Clause 35.3, if specified in BDS. These factors may be related to the characteristics, performance, and terms and conditions of purchase of the Goods and Related Services. The effect of the factors selected, if any, shall be expressed in monetary terms to facilitate comparison of bids</p> <p>35.5 If so specified in the BDS, these Bidding Documents shall allow Bidders to quote for one or more lots, and shall allow the Purchaser to award one or multiple lots to more than one Bidder. The methodology of evaluation to determine the lowest-evaluated lot combinations is specified in Section III, Evaluation and Qualification Criteria.</p>
<p>36. Comparison of Bids</p>	<p>36.1 The Purchaser shall compare all substantially responsive bids to determine the lowest-evaluated bid, in accordance with ITB Clause 35.</p>
<p>37. Post qualification of the Bidder.</p>	<p>37.1 The Purchaser shall determine to its satisfaction whether the Bidder that is selected as having submitted the lowest evaluated and substantially responsive bid is qualified to perform the Contract satisfactorily.</p> <p>37.2 The determination shall be based upon an examination of the documentary evidence of the Bidder’s qualifications submitted by the Bidder, pursuant to ITB Clause 18.</p> <p>37.3 An affirmative determination shall be a prerequisite for award of the Contract to the Bidder. A negative determination shall result in disqualification of the bid, in which event the Purchaser shall proceed to the next lowest evaluated bid to make a similar determination of that Bidder’s capabilities to perform satisfactorily.</p>
<p>38. Purchaser’s Right to Accept Any Bid, and to Reject Any or All Bids</p>	<p>38.1 The Purchaser reserves the right to accept or reject any bid, and to annul the bidding process and reject all bids at any time prior to contract award, without thereby incurring any liability to Bidders.</p>

Award of Contract	
39. Award Criteria	39.1 The Purchaser shall award the Contract to the Bidder whose offer has been determined to be the lowest evaluated bid and is substantially responsive to the Bidding Documents, provided further that the Bidder is determined to be qualified to perform the Contract satisfactorily.
40. Purchaser's Right to Vary Quantities at Time of Award	40.1 At the time the Contract is awarded, the Purchaser reserves the right to increase or decrease the quantity of Goods and Related Services originally specified in Section V, Schedule of Requirements, provided this does not exceed twenty five percent (25%) or one unit whichever is higher and without any change in the unit prices or other terms and conditions of the bid and the Bidding Documents.
41. Notification of Award	<p>41.1 Prior to the expiration of the period of bid validity, the Purchaser shall notify the successful Bidder, in writing, that its Bid has been accepted.</p> <p>41.2 Until a formal Contract is prepared and executed, the notification of award shall constitute a binding Contract.</p> <p>41.3 Upon the successful Bidder's furnishing of the signed Contract Form and performance security pursuant to ITB Clause 43, the Purchaser will promptly notify each unsuccessful Bidder and will discharge its bid security, pursuant to ITB Clause 20.4.</p>
42. Signing of Contract	<p>42.1 Within Seven (7) days after notification, the Purchaser shall complete the Agreement, and inform the successful Bidder to sign it.</p> <p>42.2 Within Seven (7) days of receipt of such information, the successful Bidder shall sign the Agreement.</p>
43. Performance Security	<p>43.1 Within fourteen (14) days of the receipt of notification of award from the Purchaser, the successful Bidder, if required, shall furnish the Performance Security in accordance with the CC, using for that purpose the Performance Security Form included in Section VIII Contract forms. The Employer shall promptly notify the name of the winning Bidder to each unsuccessful Bidder and discharge the Bid Securities of the unsuccessful bidders pursuant to ITB Sub-Clause 20.4.</p> <p>43.2 Failure of the successful Bidder to submit the abovementioned Performance Security or sign the Contract shall constitute sufficient grounds for the annulment of the award and forfeiture of the Bid Security or execution of the Bid- Securing Declaration. In that event the Purchaser may award the Contract to the next lowest evaluated Bidder, whose offer is substantially responsive and is determined by the Purchaser to be qualified to perform the Contract satisfactorily.</p>

Section VI. Conditions of Contract

1. Definitions	<p>1.1 The following words and expressions shall have the meanings hereby assigned to them:</p> <p>(a) “Contract” means the Contract Agreement entered into between the Purchaser and the Supplier, together with the Contract Documents referred to therein, including all attachments, appendices, and all documents incorporated by reference therein.</p> <p>(b) “Contract Documents” means the documents listed in the Contract Agreement, including any amendments thereto.</p> <p>(c) “Contract Price” means the price payable to the Supplier as specified in the Contract Agreement, subject to such additions and adjustments thereto or deductions therefrom, as may be made pursuant to the Contract.</p> <p>(d) “Day” means calendar day.</p> <p>(e) “Completion” means the fulfillment of the supply of Goods to the destination specified and completion of the Related Services by the Supplier in accordance with the terms and conditions set forth in the Contract.</p> <p>(f) “CC” means the Conditions of Contract.</p> <p>(g) “Goods” means all of the commodities, raw material, machinery and equipment, and/or other materials that the Supplier is required to supply to the Purchaser under the Contract.</p> <p>(h) “Purchaser” means the entity purchasing the Goods and Related Services, as specified in the Contract Data.</p> <p>(i) “Related Services” means the services incidental to the supply of the goods, such as insurance, installation, training and initial maintenance and other such obligations of the Supplier under the Contract.</p> <p>(j) “Subcontractor” means any natural person, private or government entity, or a combination of the above, to whom any part of the Goods to be supplied or execution of any part of the Related Services is subcontracted by the Supplier. Section VI General Conditions of Contract 51</p> <p>(k) “Supplier” means the natural person, private or government entity, or a combination of the above, whose bid to perform the Contract has been accepted by the Purchaser and is named as such in the Contract Agreement.</p>
-----------------------	--

	(l) "The Project Site," where applicable, means the place named in the Contract Data.
2. Contract Documents	2.1 Subject to the order of precedence set forth in the Contract Agreement, all documents forming the Contract (and all parts thereof) are intended to be correlative, complementary, and mutually explanatory. The Contract Agreement shall be read as a whole.
3. Fraud and Corruption	<p>3.1 The Government of Sri Lanka requires the Purchaser as well as bidders, suppliers, contractors, and consultants to observe the highest standard of ethics during the procurement and execution of such contracts. In pursuit of this policy:</p> <p>(i) "corrupt practice" means offering, giving, receiving, or soliciting, directly or indirectly, of anything of value to influence the action of a public official in the procurement process or in contract execution;</p> <p>(ii) "fraudulent practice" means a misrepresentation or omission of facts in order to influence a procurement process or the execution of a contract;</p> <p>(iii) "collusive practice" means a scheme or arrangement between two or more bidders, with or without the knowledge of the Purchaser to establish bid prices at artificial, noncompetitive levels; and</p> <p>(iv) "Coercive practice" means harming or threatening to harm, directly or indirectly, persons or their property to influence their participation in the procurement process or affect the execution of a contract.</p>
4. Interpretation	<p>4.1 If the context so requires it, singular means plural and vice versa.</p> <p>4.2 Entire Agreement</p> <p>The Contract constitutes the entire agreement between the Purchaser and the Supplier and supersedes all communications, negotiations and agreements (whether 52 Section VII. General Conditions of Contract written or oral) of the parties with respect thereto made prior to the date of Contract.</p> <p>4.3 Amendment</p> <p>No amendment or other variation of the Contract shall be valid unless it is in writing, is dated, expressly refers to the Contract, and is signed by a duly authorized representative of each party thereto.</p> <p>4.4 Severability</p> <p>If any provision or condition of the Contract is prohibited or rendered invalid or unenforceable, such prohibition, invalidity or unenforceability shall not affect the validity or enforceability of any other provisions and conditions of the Contract.</p>
5. Language	5.1 The Contract as well as all correspondence and documents relating to the Contract exchanged by the Supplier and the Purchaser,

	<p>shall be written in English language. Supporting documents and printed literature that are part of the Contract may be in another language provided they are accompanied by an accurate translation of the relevant passages in the language specified, in which case, for purposes of interpretation of the Contract, this translation shall govern.</p> <p>5.2 The Supplier shall bear all costs of translation to the governing language and all risks of the accuracy of such translation, for documents provided by the Supplier.</p>
6. Joint Venture, Consortium or Association	<p>6.1 If the Supplier is a joint venture, consortium, or association, all of the parties shall be jointly and severally liable to the Purchaser for the fulfillment of the provisions of the Contract and shall designate one party to act as a leader with authority to bind the joint venture, consortium, or association. The composition or the constitution of the joint venture, consortium, or association shall not be altered without the prior consent of the Purchaser.</p>
7. Eligibility	<p>7.1 All goods supplied under this contract shall be complied with applicable standards stipulated by the Sri Lanka Standards Institute. In the absence of such standards, the Goods supplied shall be complied to other internationally accepted standards, such as British Standards.</p>
8. Notices	<p>8.1 Any notice given by one party to the other pursuant to the Contract shall be in writing to the address specified in the Contract Data. The term “in writing” means communicated in written form with proof of receipt. Section VI General Conditions of Contract 53</p> <p>8.2 A notice shall be effective when delivered or on the notice’s effective date, whichever is later.</p>
9. Governing Law	<p>9.1 The Contract shall be governed by and interpreted in accordance with the laws of the Democratic Socialist Republic of Sri Lanka.</p>
10. Settlement of Disputes	<p>10.1 The Purchaser and the Supplier shall make every effort to resolve amicably by direct informal negotiation any disagreement or dispute arising between them under or in connection with the Contract.</p> <p>10.2 If, after twenty-eight (28) days, the parties have failed to resolve their dispute or difference by such mutual consultation, then either the Purchaser or the Supplier may give notice to the other party of its intention to commence arbitration, as hereinafter provided, as to the matter in dispute, and no arbitration in respect of this matter may be commenced unless such notice is given. Any dispute or difference in respect of which a notice of intention to commence arbitration has been given in accordance with this Clause shall be finally settled by arbitration. Arbitration may be commenced prior to or after delivery of the Goods under the Contract. Arbitration proceedings shall be conducted in accordance with the Arbitration Act No: 11 of 1995.</p> <p>10.3 Notwithstanding any reference to arbitration herein,</p>

	<p>(a) the parties shall continue to perform their respective obligations under the Contract unless they otherwise agree; and</p> <p>(b) the Purchaser shall pay the Supplier any monies due the Supplier.</p>
11. Scope of Supply	11.1 The Goods and Related Services to be supplied shall be as specified in the Schedule of Requirements.
12. Delivery and Documents	12.1 Subject to CC Sub-Clause 32.1, the Delivery of the Goods and Completion of the Related Services shall be in accordance with the Delivery and Completion Schedule specified in the Schedule of Requirements. Where applicable the details of shipping and other documents to be furnished by the Supplier are specified in the Contract Data.
13. Supplier's Responsibilities	13.1 The Supplier shall supply all the Goods and Related Services included in the Scope of Supply in accordance with CC Clause 11, and the Delivery and Completion Schedule, as per CC Clause 12.
14. Contract Price	14.1 Prices charged by the Supplier for the Goods supplied and the Related Services performed under the Contract shall not vary from the prices quoted by the Supplier in its bid.
15. Terms of Payment	<p>15.1 The Contract Price shall be paid as specified in the Contract Data.</p> <p>15.2 The Supplier's request for payment shall be made to the Purchaser in writing, accompanied by invoices describing, as appropriate, the Goods delivered and Related Services performed, and by the documents submitted pursuant to CC Clause 12 and upon fulfillment of all other obligations stipulated in the Contract.</p> <p>15.3 Payments shall be made promptly by the Purchaser, but in no case later than twenty eight (28) days after submission of an invoice or request for payment by the Supplier, and after the Purchaser has accepted it.</p>
16. Taxes and Duties	16.1 The Supplier shall be entirely responsible for all taxes, duties, license fees, etc., incurred until delivery of the contracted Goods to the Purchaser.
17. Performance Security	<p>17.1 If required as specified in the Contract Data, the Supplier shall, within fourteen (14) days of the notification of contract award, provide a performance security of Ten percent (10%) of the Contract Price for the performance of the Contract.</p> <p>17.2 The proceeds of the Performance Security shall be payable to the Purchaser as compensation for any loss resulting from the Supplier's failure to complete its obligations under the Contract.</p> <p>17.3 As specified in the Contract Data, the Performance Security, if required, shall be in Sri Lanka Rupees and shall be in the format stipulated by the Purchaser in the Contract Data, or in another format acceptable to the Purchaser.</p> <p>17.4 The Performance Security shall be discharged by the Purchaser</p>

	and returned to the Supplier not later than twenty-eight (28) days following the date of Completion of the Supplier's performance obligations under the Contract, including any warranty obligations.
18. Copyright	18.1 The copyright in all drawings, documents, and other materials containing data and information furnished to the Purchaser by the Supplier herein shall remain vested in the Supplier, or, if they are furnished to the Purchaser directly or through the Supplier by any third party, including suppliers of materials, the copyright in such materials shall remain vested in such third party.
19. Confidential Information	<p>19.1 The Purchaser and the Supplier shall keep confidential and shall not, without the written consent of the other party hereto, divulge to any third party any documents, data, or other information furnished directly or indirectly by the other party hereto in connection with the Contract, whether such information has been furnished prior to, during or following completion or termination of the Contract. Notwithstanding the above, the Supplier may furnish to its Subcontractor such documents, data, and other information it receives from the Purchaser to the extent required for the Subcontractor to perform its work under the Contract, in which event the Supplier shall obtain from such Subcontractor an undertaking of confidentiality similar to that imposed on the Supplier under CC Clause 19.</p> <p>19.2 The Purchaser shall not use such documents, data, and other information received from the Supplier for any purposes unrelated to the contract. Similarly, the Supplier shall not use such documents, data, and other information received from the Purchaser for any purpose other than the performance of the Contract.</p> <p>19.3 The above provisions of CC Clause 19 shall not in any way modify any undertaking of confidentiality given by either of the parties hereto prior to the date of the Contract in respect of the Supply or any part thereof.</p> <p>19.4 The provisions of CC Clause 19 shall survive completion or termination, for whatever reason, of the Contract.</p>
20. Subcontracting	<p>20.1 The Supplier shall notify the Purchaser in writing of all subcontracts awarded under the Contract if not already specified in the bid. Such notification, in the original bid or later shall not relieve the Supplier from any of its obligations, duties, responsibilities, or liability under the Contract.</p> <p>20.2 Subcontracts shall comply with the provisions of CC Clauses 3 and 7.</p>
21. Specifications and Standards	<p>21.1 Technical Specifications and Drawings</p> <p>(a) The Goods and Related Services supplied under this Contract shall conform to the technical specifications and standards mentioned in Section V, Schedule of Requirements and, when no applicable standard is mentioned, the standard shall be equivalent or superior to the official standards whose application is appropriate to the Goods' country of origin.</p>

	<p>(b) The Supplier shall be entitled to disclaim responsibility for any design, data, drawing, specification or other document, or any modification thereof provided or designed by or on behalf of the Purchaser, by giving a notice of such disclaimer to the Purchaser.</p> <p>(c) Wherever references are made in the Contract to codes and standards in accordance with which it shall be executed, the edition or the revised version of such codes and standards shall be those specified in the Schedule of Requirements. During Contract execution, any changes in any such codes and standards shall be applied only after approval by the Purchaser and shall be treated in accordance with CC Clause 32.</p>
22. Packing and Documents	22.1 The Supplier shall pack the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in the Contract.
23. Insurance	23.1 Unless otherwise specified in the Contract Data, the Goods supplied under the Contract shall be fully insured against loss or damage incidental to manufacture or acquisition, transportation, storage, and delivery.
24. Transportation	24.1 Unless otherwise specified in the Contract Data, responsibility for arranging transportation of the Goods shall be a responsibility of the supplier.
25. Inspections and Tests	<p>25.1 The Supplier shall at its own expense and at no cost to the Purchaser carry out all such tests and/or inspections of the Goods and Related Services as are specified in the Contract Data.</p> <p>25.2 The inspections and tests may be conducted on the premises of the Supplier or its Subcontractor, at point of delivery, and/or at the Goods' final destination, or in another place as specified in the Contract Data. Subject to CC Sub-Clause 25.3, if conducted on the premises of the Supplier or its Subcontractor, all reasonable facilities and assistance, including access to drawings and production data, shall be furnished to the inspectors at no charge to the Purchaser.</p> <p>25.3 The Purchaser or its designated representative shall be entitled to attend the tests and/or inspections referred to in CC Sub-Clause 25.2, provided that the Purchaser bear all of its own costs and expenses incurred in connection with such attendance including, but not limited to, all traveling and board and lodging expenses.</p> <p>25.4 Whenever the Supplier is ready to carry out any such test and inspection, it shall give a reasonable advance notice, including the place and time, to the Purchaser. The Supplier shall obtain from any relevant third party or manufacturer any necessary permission or consent to enable the Purchaser or its designated representative to attend the test and/or inspection.</p> <p>25.5 The Purchaser may require the Supplier to carry out any test and/or inspection not required by the Contract but deemed necessary to verify that the characteristics and performance of the Goods</p>

	<p>comply with the technical specifications codes and standards under the Contract, provided that the Supplier's reasonable costs and expenses incurred in the carrying out of such test and/or inspection shall be added to the Contract Price. Further, if such test and/or inspection impede the progress of manufacturing and/or the Supplier's performance of its other obligations under the Contract, due allowance will be made in respect of the Delivery Dates and Completion Dates and the other obligations so affected.</p> <p>25.6 The Supplier shall provide the Purchaser with a report of the results of any such test and/or inspection.</p> <p>25.7 The Purchaser may reject any Goods or any part thereof that fail to pass any test and/or inspection or do not conform to the specifications. The Supplier shall either rectify or replace such rejected Goods or parts thereof or make alterations necessary to meet the specifications at no cost to the Purchaser, and shall repeat the test and/or inspection, at no cost to the Purchaser, upon giving a notice pursuant to CC Sub-Clause 25.4.</p> <p>25.8 The Supplier agrees that neither the execution of a test and/or inspection of the Goods or any part thereof, nor the attendance by the Purchaser or its representative, nor the issue of any report pursuant to CC Sub-Clause 25.6, shall release the Supplier from any warranties or other obligations under the Contract.</p>
<p>26. Liquidated Damages</p>	<p>26.1 Except as provided under CC Clause 31, if the Supplier fails to deliver any or all of the Goods by the Date(s) of delivery or perform the Related Services within the period specified in the Contract, the Purchaser may without prejudice to all its other remedies under the Contract, deduct from the Contract Price, as liquidated damages, a sum equivalent to the percentage specified in the Contract Data of the delivered price of the delayed Goods or unperformed Services for each week or part thereof of delay until actual delivery or performance, up to a 58 Section VII. General Conditions of Contract maximum deduction of the percentage specified in those Contract Data. Once the maximum is reached, the Purchaser may terminate the Contract pursuant to CC Clause 34.</p>
<p>27. Warranty</p>	<p>27.1 The Supplier warrants that all the Goods are new, unused, and of the most recent or current models, and that they incorporate all recent improvements in design and materials, unless provided otherwise in the Contract.</p> <p>27.2 Subject to CC Sub-Clause 21.1(b), the Supplier further warrants that the Goods shall be free from defects arising from any act or omission of the Supplier or arising from design, materials, and workmanship, under normal use in the conditions prevailing in the country of final destination.</p> <p>27.3 Unless otherwise specified in the Contract Data, the warranty shall remain valid for twelve (12) months after the Goods, or any portion thereof as the case may be, have been delivered to and</p>

	<p>accepted at the final destination indicated in the Contract Data.</p> <p>27.4 The Purchaser shall give notice to the Supplier stating the nature of any such defects together with all available evidence thereof, promptly following the discovery thereof. The Purchaser shall afford all reasonable opportunity for the Supplier to inspect such defects.</p> <p>27.5 Upon receipt of such notice, the Supplier shall, within the period specified in the Contract Data, expeditiously repair or replace the defective Goods or parts thereof, at no cost to the Purchaser.</p> <p>27.6 If having been notified, the Supplier fails to remedy the defect within the period specified in the Contract Data, the Purchaser may proceed to take within a reasonable period such remedial action as may be necessary, at the Supplier's risk and expense and without prejudice to any other rights which the Purchaser may have against the Supplier under the Contract.</p>
<p>28. Patent Indemnity</p>	<p>28.1 The Supplier shall, subject to the Purchaser's compliance with CC Sub-Clause 28.2, indemnify and hold harmless the Purchaser and its employees and officers from and against any and all suits, actions or administrative proceedings, claims, demands, losses, damages, costs, and expenses of any nature, including attorney's fees and expenses, which the Purchaser may suffer as a result of any infringement or alleged infringement of any patent, utility model, registered design, trademark, copyright, or other intellectual property right registered or otherwise existing at the date of the contract by reason of:</p> <p>(a) the installation of the Goods by the Supplier or the use of the Goods in the country where the Site is located; and</p> <p>(b) The sale in any country of the products produced by the Goods. Such indemnity shall not cover any use of the Goods or any part thereof other than for the purpose indicated by or to be reasonably inferred from the Contract, neither any infringement resulting from the use of the Goods or any part thereof, or any products produced thereby in association or combination with any other equipment, plant, or materials not supplied by the Supplier, pursuant to the Contract.</p> <p>28.2 If any proceedings are brought or any claim is made against the Purchaser arising out of the matters referred to in CC Sub-Clause 28.1, the Purchaser shall promptly give the Supplier a notice thereof, and the Supplier may at its own expense and in the Purchaser's name conduct such proceedings or claim and any negotiations for the settlement of any such proceedings or claim.</p> <p>28.3 If the Supplier fails to notify the Purchaser within twenty eight (28) days after receipt of such notice that it intends to conduct any such proceedings or claim, then the Purchaser shall be free to conduct</p>

	<p>the same on its own behalf.</p> <p>28.4 The Purchaser shall, at the Supplier’s request, afford all available assistance to the Supplier in conducting such proceedings or claim, and shall be reimbursed by the Supplier for all reasonable expenses incurred in so doing.</p> <p>28.5 The Purchaser shall indemnify and hold harmless the Supplier and its employees, officers, and Subcontractors from and against any and all suits, actions or administrative proceedings, claims, demands, losses, damages, costs, and expenses of any nature, including attorney’s fees and expenses, which the Supplier may suffer as a result of any infringement or alleged infringement of any patent, utility model, registered design, trademark, copyright, or other intellectual property right registered or otherwise existing at the date of the Contract arising out of or in connection with any design, data, drawing, specification, or other documents or materials provided or designed by or on behalf of the Purchaser.</p>
<p>29. Limitation of Liability</p>	<p>29.1 Except in cases of criminal negligence or willful misconduct,</p> <p>(a) the Supplier shall not be liable to the Purchaser, whether in contract, tort, or otherwise, for any indirect or consequential loss or damage, loss of use, loss of production, or loss of profits or interest costs, provided that this exclusion shall not apply to any obligation of the Supplier to pay liquidated damages to the Purchaser and</p> <p>(b) the aggregate liability of the Supplier to the Purchaser, whether under the Contract, in tort or otherwise, shall not exceed the total Contract Price, provided that this limitation shall not apply to the cost of repairing or replacing defective equipment, or to any obligation of the supplier to indemnify the purchaser with respect to patent infringement</p>
<p>30. Change in Laws and Regulations</p>	<p>30.1 Unless otherwise specified in the Contract, if after the date of 28 days prior to date of Bid submission, any law, regulation, ordinance, order or bylaw having the force of law is enacted, promulgated, abrogated, or changed in Sri Lanka that subsequently affects the Delivery Date and/or the Contract Price, then such Delivery Date and/or Contract Price shall be correspondingly increased or decreased, to the extent that the Supplier has thereby been affected in the performance of any of its obligations under the Contract. Notwithstanding the foregoing, such additional or reduced cost shall not be separately paid or credited if the same has already been accounted for in the price adjustment provisions where applicable, in accordance with CC Clause 14.</p>

<p>31. Force Majeure</p>	<p>31.1 The Supplier shall not be liable for forfeiture of its Performance Security, liquidated damages, or termination or default if and to the extent that it's delay in performance or other failure to perform its obligations under the Contract is the result of an event of Force Majeure.</p> <p>31.2 For purposes of this Clause, "Force Majeure" means an event or situation beyond the control of the Supplier that is not foreseeable, is unavoidable, and its origin is not due to negligence or lack of care on the part of the Supplier. Such events may include, but not be limited to, acts of the Purchaser in its sovereign capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions, and freight embargoes.</p> <p>31.3 If a Force Majeure situation arises, the Supplier shall promptly notify the Purchaser in writing of such condition and the cause thereof. Unless otherwise directed by the Purchaser in writing, the Supplier shall continue to perform its obligations under the Contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force Majeure event.</p>
<p>32. Change Orders and Contract Amendments</p>	<p>32.1 The Purchaser may at any time order the Supplier through notice in accordance CC Clause 8, to make changes within the general scope of the Contract in any one or more of the following:</p> <p>(a) drawings, designs, or specifications, where Goods to be furnished under the Contract are to be specifically manufactured for the Purchaser;</p> <p>(b) the method of shipment or packing;</p> <p>(c) the place of delivery; and</p> <p>(d) The Related Services to be provided by the Supplier. 32.2 If any such change causes an increase or decrease in the cost of, or the time required for, the Supplier's performance of any provisions under the Contract, an equitable adjustment shall be made in the Contract Price or in the Delivery/Completion Schedule, or both, and the Contract shall accordingly be amended. Any claims by the Supplier for adjustment under this Clause must be asserted within twenty-eight (28) days from the date of the Supplier's receipt of the Purchaser's change order.</p> <p>32.3 Prices to be charged by the Supplier for any Related Services that might be needed but which were not included in the Contract shall be agreed upon in advance by the parties and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.</p> <p>32.4 Subject to the above, no variation in or modification of the terms of the Contract shall be made except by written amendment signed by the parties.</p>

<p>33. Extensions of Time</p>	<p>33.1 If at any time during performance of the Contract, the Supplier or its subcontractors should encounter conditions impeding timely delivery of the Goods or completion of Related Services pursuant to CC Clause 12, the Supplier shall promptly notify the Purchaser in writing of the delay, its likely duration, and its cause. As soon as practicable after receipt of the Supplier's notice, the Purchaser shall evaluate the situation and may at its discretion extend the Supplier's time for performance, in which case the extension shall be ratified by the parties by amendment of the Contract.</p> <p>33.2 Except in case of Force Majeure, as provided under CC Clause 31, a delay by the Supplier in the performance of its Delivery and Completion obligations shall render the Supplier liable to the imposition of liquidated damages pursuant to CC Clause 26, unless an extension of time is agreed upon, pursuant to CC Sub-Clause 33.1.</p>
<p>34. Termination</p>	<p>34.1 Termination for Default</p> <p>(a) The Purchaser, without prejudice to any other remedy for breach of Contract, by written notice of default sent to the Supplier, may terminate the Contract in whole or in part:</p> <p>(i) if the Supplier fails to deliver any or all of the Goods within the period specified in the Contract, or within any extension thereof granted by the Purchaser pursuant to CC Clause 33;</p> <p>(ii) if the Supplier fails to perform any other obligation under the Contract; or</p> <p>(iii) If the Supplier, in the judgment of the Purchaser has engaged in fraud and corruption, as defined in CC Clause 3, in competing for or in executing the Contract.</p> <p>(b) In the event the Purchaser terminates the Contract in whole or in part, pursuant to CC Clause 34.1(a), the Purchaser may procure, upon such terms and in such manner as it deems appropriate, Goods or Related Services similar to those undelivered or not performed, and the Supplier shall be liable to the Purchaser for any additional costs for such similar Goods or Related Services. However, the Supplier shall continue performance of the Contract to the extent not terminated.</p> <p>34.2 Termination for Insolvency.</p> <p>(a) The Purchaser may at any time terminate the Contract by giving notice to the Supplier if the Supplier becomes bankrupt or otherwise insolvent. In such event, termination will be without compensation to the Supplier, provided that such termination will not prejudice or affect any right of action or remedy that has accrued or will accrue thereafter to the Purchaser</p>

	<p>34.3 Termination for Convenience.</p> <p>(a) The Purchaser, by notice sent to the Supplier, may terminate the Contract, in whole or in part, at any time for its convenience. The notice of termination shall specify that termination is for the Purchaser's convenience, the extent to which performance of the Supplier under the Contract is terminated, and the date upon which such termination becomes effective.</p> <p>(b) The Goods that are complete and ready for shipment within twenty-eight (28) days after the Supplier's receipt of notice of termination shall be accepted by the Purchaser at the Contract terms and prices. For the remaining Goods, the Purchaser may elect:</p> <p>(i) to have any portion completed and delivered at the Contract terms and prices; and/or</p> <p>(ii) to cancel the remainder and pay to the Supplier an agreed amount for partially completed Goods and Related Services and for materials and parts previously procured by the Supplier.</p>
35. Assignment	<p>35.1 Neither the Purchaser nor the Supplier shall assign, in whole or in part, their obligations under this Contract, except with prior written consent of the other party.</p>

Section VIII.

Contract Forms

1. Contract Agreement

THIS CONTRACT AGREEMENT is made

the [insert: number] day of [insert: month], [insert: year].

BETWEEN

(1) [insert complete name of Purchaser], a [insert description of type of legal entity, for example, an agency of the Ministry of or corporation and having its principal place of business at [insert address of Purchaser] (hereinafter called “the Purchaser”), and

(2) [insert name of Supplier], a corporation incorporated under the laws of [insert: country of Supplier] and having its principal place of business at [insert: address of Supplier] (hereinafter called “the Supplier”).

WHEREAS the Purchaser invited bids for certain Goods and ancillary services, viz., [insert brief description of Goods and Services] and has accepted a Bid by the Supplier for the supply of those Goods and Services in the sum of [insert Contract Price in words and figures, expressed in the Contract currency (ies)] (hereinafter called “the Contract Price”).

NOW THIS AGREEMENT WITNESSETH AS FOLLOWS:

1. In this Agreement words and expressions shall have the same meanings as are respectively assigned to them in the Conditions of Contract referred to.

2. The following documents shall constitute the Contract between the Purchaser and the Supplier, and each shall be read and construed as an integral part of the Contract:

(a) This Contract Agreement

(b) Contract Data

(c) Conditions of Contract

(d) Technical Requirements (including Schedule of Requirements and Technical Specifications)

(e) The Supplier’s Bid and original Price Schedules

(f) The Purchaser’s Notification of Award

(g) [Add here any other document(s)]

3. This Contract shall prevail over all other Contract documents. In the event of any discrepancy or inconsistency within the Contract documents, then the documents shall prevail in the order listed above.

4. In consideration of the payments to be made by the Purchaser to the Supplier as hereinafter mentioned, the Supplier hereby covenants with the Purchaser to provide the Goods and Services and to remedy defects therein in conformity in all respects with the provisions of the Contract.

5. The Purchaser hereby covenants to pay the Supplier in consideration of the provision of the Goods and Services and the remedying of defects therein, the Contract Price or such other sum as may become payable under the provisions of the Contract at the times and in the manner prescribed by the Contract.

IN WITNESS whereof the parties hereto have caused this Agreement to be executed in accordance with the laws of Democratic Socialist Republic of Sri Lanka on the day, month and year indicated above.

For and on behalf of the Purchaser

Signed: [insert signature]

in the capacity of [insert title or other appropriate designation]

in the presence of [insert identification of official witness]

For and on behalf of the Supplier

Signed: [insert signature of authorized representative(s) of the Supplier]

in the capacity of [insert title or other appropriate designation]

in the presence of [insert identification of official witness]

2. Performance Security

[The issuing agency, as requested by the successful Bidder, shall fill in this form in accordance with the instructions indicated] ----- [Issuing Agency's Name, and Address of Issuing Branch or Office] ----- * Beneficiary: -----
- [Name and Address of Employer] -----

Date: -----

PERFORMANCE GUARANTEE No.: -----

We have been informed that ----- [name of Supplier] (hereinafter called "the Supplier") has entered into Contract No. ----- [Reference number of the contract] dated ----- with you, for the ----- Supply of ----- [name of contract and brief description] (hereinafter called "the Contract").

Furthermore, we understand that, according to the conditions of the Contract, a performance guarantee is required. At the request of the Supplier, we ----- [name of Agency] hereby irrevocably undertake to pay you any sum or sums not exceeding in total an amount of -----

[amount in figures] (-----) [amount in words], such sum being payable in the types and proportions of currencies in which the Contract Price is payable, upon receipt by us of your first demand in writing accompanied by a written statement stating that the Contractor is in breach of its obligation(s) under the Contract, without your needing to prove or to show grounds for your demand or the sum specified therein. This guarantee shall expire, no later than the day of, 20.. [insert date, 28 days beyond the scheduled completion date including the warranty period] and any demand for payment under it must be received by us at this office on or before that date.

[Signature(s)]

3. Guarantee for Advance Payment

[The issuing agency, as requested by the successful Bidder, shall fill in this form in accordance with the instructions indicated.]

Date: [insert date (as day, month, and year) of Bid Submission] ICB No. and title: [insert number and title of bidding process] [issuing agency's letterhead] Beneficiary: [insert legal name and address of Purchaser]

ADVANCE PAYMENT GUARANTEE No.: [insert Advance Payment Guarantee no.]

We, [insert legal name and address of issuing agency], have been informed that [insert complete name and address of Supplier] (hereinafter called "the Supplier") has entered into Contract No. [Insert number] dated [insert date of Agreement] with you, for the supply of [insert types of Goods to be delivered] (hereinafter called "the Contract").

Furthermore, we understand that, according to the conditions of the Contract, an advance is to be made against an advance payment guarantee.

At the request of the Supplier, we hereby irrevocably undertake to pay you any sum or sums not exceeding in total an amount of [insert amount(s) in figures and words] upon receipt by us of your first demand in writing declaring that the Supplier is in breach of its obligation under the Contract because the Supplier used the advance payment for purposes other than toward delivery of the Goods.

It is a condition for any claim and payment under this Guarantee to be made that the advance payment referred to above must have been received by the Supplier on its account [insert number and domicile of the account]

This Guarantee shall remain valid and in full effect from the date of the advance payment received by the Supplier under the Contract until [insert date].

[Signature of authorized representative(s) of the issuing agency]

Section II.

Bidding Data Sheet (BDS)

The following specific data for the goods to be procured shall complement, supplement, or amend the provisions in the Instructions to Bidders (ITB). Whenever there is a conflict, the provisions herein shall prevail over those in ITB.

[Instructions for completing the Bid Data Sheet are provided, as needed, in the relevant ITB Clauses.]

ITB Clause Reference	A. General
ITB 1.1	The Purchaser is: University of Jaffna
ITB 1.1	The name and identification number of the Contract are: “Supply of Mechanical & Civil Engineering Equipment, University of Jaffna – Package 01 - UJ/F/PO/T/03/2016”
ITB 1.2	The bidder should have at least three years experience in the relevant industry in Sri Lanka and should submit documents to prove experience in the industry.
ITB 2.1	The source of funding is: GOSL
ITB 4.4	Foreign bidders are allowed to participate in bidding: Not allowed
	B. Contents of Bidding Documents
ITB 7.1	For Clarification of bid purposes only, the Purchaser’s address is: Attention: SeniorAssistant Bursar/Supplies Address: 57, University of Jaffna, Thirunelvely, Jaffna Telephone: 021-2220962 Electronic mail address:bursaruj@gmail.com
	C. Preparation of Bids
ITB 11.1 (e)	The Bidder shall submit the following additional documents: A complete company profile of the bidders including, but not limited to, the following: <ul style="list-style-type: none"> • Data commencing business in Sri Lanka • Names of current Directors • Annual turnover, assets and liabilities • List of client who use the products • Number of staff supporting to proceed the operation in Sri Lanka and their competence • Past 3 years relevant experience in the relevant industry in Sri Lanka

ITB 15.1	The bidder shall quote the local expenditure in Sri Lankan Rupees.
ITB 18.1 (b)	After sales service is: required
ITB 19.1	The bid shall be validity until: 23.09.2016
ITB 20.1	(a) Bid shall include a Bid Security (issued by bank or surety) included in Section IV Bidding Forms;
ITB 20.2	The amount of the Bid Security shall be: As per the advertisement Beneficiary: Vice Chancellor, University of Jaffna. The validity period of the bid security shall be until: 24.10.2016
	D. Submission and Opening of Bids
ITB 22.2 (c)	The inner and outer envelopes shall bear the following identification marks: “Supply of Mechanical & Civil Engineering Equipment, University of Jaffna – Package 01 - UJ/F/PO/T/03/2016”
ITB 23.1	For bid submission purposes, the Purchaser’s address is: Attention: Bursar Address: University of Jaffna, P.O.Box 57, Thirunelvely, Jaffna. The deadline for the submission of bids is: Date: 23.06.2016 Time: 2.00pm
ITB 26.1	The bid opening shall take place at: Address: Board Room, University of Jaffna, P.O.Box 57, Thirunelvely, Jaffna. Date: 23.06.2016 Time: 2.00 pm
	E. Evaluation and Comparison of Bids
ITB 34.1	Domestic preference shall not be a bid evaluation factor.
ITB 35.3(d)	The adjustments shall be determined using the following criteria, from amongst those set out in Section III, Evaluation and Qualification Criteria: (a) Deviation in Delivery schedule:

	<p>Option 2 is selected and the adjustment is 0.5% per week or part thereof</p> <p>(b) Deviation in payment schedule: Not applicable</p> <p>(c) the cost of major replacement components, mandatory spare parts, and service: Not applicable</p>
ITB 35.4	The following factors and methodology will be used for evaluation: Not applicable
ITB 35.5	Bidders shall be allowed to quote for one or more lots. [refer to Section III Evaluation and Qualification Criteria] Purchaser will evaluate the bid item by item basis.


M. G. L. Maveekumbura
 Senior Assistant Bursar (Supplies)
 University of Jaffna
 Jaffna

Section III.

Evaluation and Qualification Criteria

1. Evaluation Criteria (ITB 35.3 (d))

The Purchaser's evaluation of a bid may take into account, in addition to the Bid Price quoted in accordance with ITB Clause 14, one or more of the following factors as specified in ITB Sub-Clause 35.3(d) and in BDS referring to ITB 35.3(d), using the following criteria and methodologies.

(a) Delivery schedule

Option 2

The goods covered under this invitation are required to be delivered within an acceptable range of weeks specified in the Schedule of Requirement. No credit will be given to earlier deliveries, and bids offering delivery beyond this range will be treated as nonresponsive. Within this acceptable range, an adjustment per week, as specified in the Bid Data Sheet, will be added for evaluation purposes only, to the bid price of bids offering deliveries later than the earliest delivery period specified in the Section V, Schedule of Requirements

(a) Deviation in payment schedule. **Not applicable**

(c) Cost of major replacement components, mandatory spare parts, and service: **Not applicable**

(d) Specific additional criteria: **None**

2. Evaluation Criteria (ITB 35.4)

3. Multiple Contracts (ITB 35.5)

The Purchaser shall award multiple contracts to the Bidder that offers the lowest evaluated combination of bids (one contract per bid) and meets the post-qualification criteria (this Section III, Sub-Section ITB 37.2 Post-Qualification Requirements)

The Purchaser shall:

(a) Evaluate only lots or contracts that include items per lot and quantity per item

(b) Take into account: The lowest-evaluated bid for each lot

3. Post qualification Requirements (ITB 37.2)

After determining the lowest-evaluated bid in accordance with ITB Sub-Clause 36.1, the Purchaser shall carry out the post qualification of the Bidder in accordance with ITB Clause 37, using only the requirements specified. Requirements not included in the text below shall not be used in the evaluation of the Bidder's qualifications.

Qualification Criteria:

- (a) Bid may be submitted by any reputed supplier of **Mechanical & Civil Engineering Equipment** registered business in Sri Lanka or any accredited local agent who takes fullest responsibility for the whole bid. The local agent shall submit evidence of status, obligations, power of attorney and any other documentary evidence that he is duly authorized and eligible to bid on behalf of the manufacturer.
- (b) The bidders should also have previous experience of at least three years in relevant industry in the supply and also technical and financial capability necessary to perform the contract.
- (c) Bids will be rejected as non- responsive if documentary evidence in proof of above has not been provided.
- (d) If an Agent submits bids on behalf of more than one supplier, unless each such bid is accompanied by a separate Bid Form for each bid, and a bid security when required for each bid, and authorization from the respective Manufacturer, and valid vendor certificate, all such bids will be rejected as non- responsive.
- (e) Bidders should possess the Certificate of Business Registration issued by a Governmental Authority/ Registrar of Companies/ Provincial Registrar of Business in the relevant category.
- (f) Bidders offering goods under their own brand names should provide along with their bids a current certification/s of quality; Bid not complying with this requirement may be treated as non - responsive.
- (g) Having a service center in Jaffna will be considered as an added qualification.

4. Domestic Preference (ITB 34.1) – **Not applicable**

Section IV

Bidding Forms

Bid Submission Form.

[The Bidder shall fill in this Form in accordance with the instructions indicated no alterations to its format shall be permitted and no substitutions shall be accepted.]

Date:

No:

To: **University of Jaffna**

We, the undersigned, declare that:

- a) We have examined and have no reservations to the Bidding Documents, including Addenda No.:
- b) We offer to supply in conformity with the Bidding Documents and in accordance with the Delivery Schedules specified in the Schedule of Requirements the following Goods and Related Service Supply of **Mechanical & Civil Engineering Equipment** to the University of Jaffna.
- c) The total price of our Bid without VAT, including any discounts offered is:
- d) The total price of our Bid including VAT, and any discounts offered is:
- e) Our bid shall be valid for the period of time specified in ITB sub-Clause 19.1, from the date fixed for the bid submission deadline in accordance with ITB Sub-Clause 23.1, and it shall remain binding upon us and may be accepted at any time before the expiration of that period;
- f) If our bid is accepted, we commit to obtain a performance security in accordance with ITB Clause 43 and CC Clause 17 for the due performance of the Contract;
- g) We have no conflict of interest in accordance with ITB Sub-Clause 4.3;
- h) Our firm, its affiliates or subsidiaries- including any subcontractors or suppliers for any part of the contract-has not been declared blacklisted by the National Procurement Agency;
- i) We understand that bid, together with your written acceptance thereof include in your notification of award, shall constitute a binding contract between us, until a formal contract is prepared and executed.

j) We understand that you are not bound to accept the lowest evaluated bid or any other bid that you may receive.

Signed:

In the capacity of

Name:

Duly authorized to sign the bid for and on behalf of:

Dated on ----- day of -----


M. G. L. Maveekumbura
Senior Assistant Bursar (Supplies)
University of Jaffna
Jaffna

Price Schedule *

No	Description of the Item and Item Code	(1)	(2)	(3)	(4)	(5)
		Qty	Unit Rate	VAT	Price with VAT (2+3)	Total (1x4)
Package 01- Mechanical & Civil Engineering Equipment						
1. Mechanical Engineering Equipment (thermodynamics)						
1.1.1	Automotive diesel engine	01				
1.1.2	Gasoline engine	01				
1.1.3	Free and forced convection apparatus	01				
1.1.4	Heat conduction and convection apparatus	01				
1.1.5	Combined convection and radiation	01				
1.1.6	Universal vibration apparatus	01				
1.1.7	Universal moulding machine	01				
1.1.8	Balancing of reciprocating Mass	01				
1.1.9	Twin Rotor System	01				
1.1.10	Optical comparator	01				
2. Mechanical Engineering Equipment (Pneumatic systems)						
1.2.1	Two - stage compressor test set	01				
1.2.2	Multi-pump test rig	01				
1.2.3	Pelton turbine test rig	01				
1.2.4	Axial flow turbine test rig	01				
1.2.5	Free and forced vortex apparatus	01				
1.2.6	Centrifugal pumps characteristics	01				
1.2.7	Basic pneumatics training kit	01				
1.2.8	Basic Electropneumatic Training Kit	01				
1.2.9	Basic Hydraulics Training Kit	01				
1.2.10	PLC Trainer Kit	01				
1.2.11	Ball and Plate Control System	01				
3. Mechanical Engineering Equipment (Workshop items)						
1.3.1	MIG welding machine	01				
1.3.2	TIG welding machine	01				
1.3.3	Metallography specimen grinding & polishing machine	01				
1.3.4	Sheet Metal Arc Welding	01				
1.3.5	Hot Metal Press Machine	01				
4. Civil Engineering Equipment (Transportation)						
1.4.1	Marshall Stability And Flow And Accessories	01				
1.4.2	Water Bath To Keep Asphalt Specimens Before Marshall Test	01				

1.4.3	Asphalt Mix Compaction Mould And Accessories	03				
1.4.4	Ring And Ball Apparatus And Accessories	01				
1.4.5	Penetration Test And Accessories	01				
1.4.6	Ductility Testing Machine (Electrically Operated)	01				
5. Civil Engineering Equipment (Geotechnical & Concrete)						
1.5.1	Proctor Compaction Mould And Rammer	03				
1.5.2	CBR Test Machine	01				
1.5.3	CBR Mould And Accessories	03				
1.5.4	Dynamic Cone Penetrometer	02				
1.5.5	Casagrande Liquid Limit Device With Counter	01				
1.5.6	Linear Shrinkage Mould	06				
1.5.7	Sample Ejector	01				
1.5.8	Triaxial Machines Accessories – CU/CD System (ELE,EL25-4047)	01				
1.5.9	Motorized Pendulum Impact Testing System	01				
1.5.10	Moisture Can	100				
1.5.11	Concrete Cube Mould	25				
1.5.12	Cube Mould Tamping Bar	05				

*Use separate price schedule for options

.....
Signature and seal of the Bidder

.....
Date

Total Price without Taxes (in SLR):

Total Price without Taxes (in Words):.....

Vat Registration No:.....

Total Price with VAT:.....

Total Price with VAT (in Words):.....

Maintenance charges as a percentage after the warranty period:.....

Name of the Authorized persons:.....

Signature of the Authorized persons:.....

Date:

Bid Guarantee

[This Bank Guarantee form shall be filled in accordance with the instructions indicated in brackets]

----- [insert issuing agency's name, and address of issuing branch or office] -----
Beneficiary: ----- [name and address of Purchaser] Date: ----- [insert (by issuing agency) date] BID GUARANTEE No.: ----- [insert (by issuing agency) number] We have been informed that ----- [insert (by issuing agency) name of the Bidder; if a joint venture, list complete legal names of partners] (hereinafter called "the Bidder") has submitted to you its bid dated ----- [insert (by issuing agency) date](hereinafter called "the Bid") for the supply of [insert name of Supplier] under Invitation for Bids No. ----- [insert IFB number] ("the IFB").

Furthermore, we understand that, according to your conditions, Bids must be supported by a Bid Guarantee.

At the request of the Bidder, we ----- [insert name of issuing agency] hereby irrevocably undertake to pay you any sum or sums not exceeding in total an amount of ----- [insert amount in figures] ----- [insert amount in words]) upon receipt by us of your first demand in writing accompanied by a written statement stating that the Bidder is in breach of its obligation(s) under the bid conditions, because the Bidder:

- (a) Has withdrawn its Bid during the period of bid validity specified; or
- (b) Does not accept the correction of errors in accordance with the Instructions to Bidders (hereinafter "the ITB"); or
- (c) having been notified of the acceptance of its Bid by the Purchaser during the period of bid validity, (i) fails or refuses to execute the Contract Form, if required, or (ii) fails or refuses to furnish the Performance Security, in accordance with the ITB.

This Guarantee shall expire: (a) if the Bidder is the successful bidder, upon our receipt of copies of the Contract signed by the Bidder and of the Performance Security issued to you by the Bidder; or (b) if the Bidder is not the successful bidder, upon the earlier of (i) our receipt of a copy of your notification to the Bidder that the Bidder was unsuccessful, otherwise it will remain in force up to ----- (insert date) Consequently, any demand for payment under this Guarantee must be received by us at the office on or before that date. _____signature(s) of authorized representative(s)]

Manufacturer's Authorization

[The Bidder shall require the Manufacturer to fill in this Form in accordance with the instructions indicated. This letter of authorization should be on the letterhead of the Manufacturer and should be signed by a person with the proper authority to sign documents that are binding on the Manufacturer. The Bidder shall include it in its bid, if so indicated in the BDS.]

Date: [insert date (as day, month and year) of Bid Submission]

No.: [insert number of bidding process]

To: [insert complete name of Purchaser]

WHEREAS

We [insert complete name of Manufacturer], who are official manufacturers of [insert type of goods manufactured], having factories at [insert full address of Manufacturer's factories], do hereby authorize [insert complete name of Bidder] to submit a bid the purpose of which is to provide the following Goods, manufactured by us [insert name and or brief description of the Goods], and to subsequently negotiate and sign the Contract.

We hereby extend our full guarantee and warranty in accordance with Clause 27 of the Conditions of Contract, with respect to the Goods offered by the above firm.

Signed: [insert signature(s) of authorized representative(s) of the Manufacturer]

Name: [insert complete name(s) of authorized representative(s) of the Manufacturer]

Title: [insert title]

Duly authorized to sign this Authorization on behalf of: [insert complete name of Bidder]

Dated on _____ day of _____, _____ [insert date of signing]

Section V

Schedule of Requirements

1. List of Goods and Delivery Schedule

[The Purchaser shall fill in this table, with the exception of the column “Bidder’s offered Delivery date” to be filled by the Bidder]

Item No	Description of Goods	QTY	Delivery Date			
			Final Destination as specified in BDS	Earliest Delivery Date	Latest Delivery Date	Bidder’s offered Delivery date
Package 01- Mechanical & Civil Engineering Equipment						
01. Mechanical Engineering Equipment (Thermodynamics)						
1.1.1	Automotive diesel engine	01	University of Jaffna	2 Weeks	4 Weeks	
1.1.2	Gasoline engine	01				
1.1.3	Free and forced convection apparatus	01				
1.1.4	Heat conduction and convection apparatus	01				
1.1.5	Combined convection and radiation	01				
1.1.6	Universal vibration apparatus	01				
1.1.7	Universal moulding machine	01				
1.1.8	Balancing of reciprocating Mass	01				
1.1.9	Twin Rotor System	01				
1.1.10	Optical comparator	01				
2. Mechanical Engineering Equipment (Pneumatic systems)						
1.2.1	Two - stage compressor test set	01	University of Jaffna	2 Weeks	4 Weeks	
1.2.2	Multi-pump test rig	01				
1.2.3	Pelton turbine test rig	01				
1.2.4	Axial flow turbine test rig	01				
1.2.5	Free and forced vortex apparatus	01				
1.2.6	Centrifugal pumps characteristics	01				
1.2.7	Basic pneumatics training kit	01				

1.2.8	Basic Electropneumatic Training Kit	01				
1.2.9	Basic Hydraulics Training Kit	01				
1.2.10	PLC Trainer Kit	01				
1.2.11	Ball and Plate Control System	01				
3. Mechanical Engineering Equipment (Workshop items)						
1.3.1	MIG welding machine	01	University of Jaffna	2 Weeks	4 Weeks	
1.3.2	TIG welding machine - 01	01				
1.3.3	Metallography specimen grinding & polishing machine	01				
1.3.4	Sheet Metal Arc Welding	01				
1.3.5	Hot Metal Press Machine	01				
4. Civil Engineering Equipment (Transportation)						
1.4.1	Marshall Stability And Flow And Accessories	01	University of Jaffna	2 Weeks	4 Weeks	
1.4.2	Water Bath To Keep Asphalt Specimens Before Marshall Test	01				
1.4.3	Asphalt Mix Compaction Mould And Accessories	03				
1.4.4	Ring And Ball Apparatus And Accessories	01				
1.4.5	Penetration Test And Accessories	01				
1.4.6	Ductility Testing Machine (Electrically Operated)	01				
5. Civil Engineering Equipment (Geotechnical & Concrete)						
1.5.1	Proctor Compaction Mould And Rammer	03	University of Jaffna	2 Weeks	4 Weeks	
1.5.2	CBR Test Machine	01				
1.5.3	CBR Mould And Accessories	03				
1.5.4	Dynamic Cone Penetrometer	02				
1.5.5	Casagrande Liquid Limit Device With Counter	01				
1.5.6	Linear Shrinkage Mould	06				
1.5.7	Sample Ejector	01				
1.5.8	Triaxial Machines Accessories – CU/CD System (ELE,EL25-4047)	01				
1.5.9	Motorized Pendulum Impact Testing System	01				
1.5.10	Moisture Can	100				
1.5.11	Concrete Cube Mould	25				
1.5.12	Cube Mould Tamping Bar	05				

* Destination of delivery: - Faculty of Engineering,
University of Jaffna,
Ariviyal Nagar,
Kilinochchi

2. Technical Specifications

The bidder shall follow the following technical requirement and other requirement.

Item No	Name and Minimum Specifications	Qty	Remarks
1.1.1	Automotive diesel engine	01	
	<ul style="list-style-type: none"> - A 4-cylinder, water cooled, Biodiesel compatible, diesel engine - Variable load eddy current dynamometer - Strong steel framework support - Computer controlled starter, throttle and dynamometer. - Engine indicator for measuring cylinder pressure - Electrical supply: 220-240V, single phase - Cooling water supply: 6 - 8 l/min at 3 bar pressure - Safety: <ul style="list-style-type: none"> - Guard protection for moving parts. - Safety interlocks - Emergency stops <p>Technical specifications</p> <p>Engine data:</p> <p>Engine Model</p> <ul style="list-style-type: none"> - Power (45 – 50) kW - Displacement: 1850cc – 1900cc - Bore: 75 - 80 mm - Stroke: 90 - 100 mm - Cylinders: 4 <p>Dynamometer data:</p> <ul style="list-style-type: none"> - Dynamometer type: Eddy Current - Cooling: Air cooled <p>Instrumentation and sensors:</p> <ul style="list-style-type: none"> - Engine speed - Torque - Inlet air flow - Inlet air temperature - Cooling water flow and temperatures (inlet and outlet) <ul style="list-style-type: none"> - Educational data acquisition and control software is needed. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures’ authorization should be submitted with the tender documents. 		

1.1.2	Gasoline engine	01	
	<ul style="list-style-type: none"> - High efficiency, three cylinder, water cooled, normally aspirated engine - Biofuel Compatible. - Variable load, eddy current dynamometer - Ignition and Injection Control system - Strong steel framework support - Remotely controlled throttle and brake load. - Engine Indicator set for production of real time P-V diagram. - Electrical supply: 220-240V, single phase - Cooling water supply: 6 - 8 l/min at 3 bar pressure - Safety: <ul style="list-style-type: none"> - Guard protection for moving parts. - Safety interlocks - Emergency stops <p>Technical specifications</p> <p>Engine data:</p> <ul style="list-style-type: none"> - Power (35 – 45) kW - Displacement: 1190cc – 1200cc - Bore: 75 – 80 mm - Stroke: 85 - 90 mm - Cylinders: 3 (6 valve) <p>Dynamometer data</p> <ul style="list-style-type: none"> - Dynamometer type: Eddy Current - Cooling: Air cooled <p>Instrumentation and sensors</p> <ul style="list-style-type: none"> - Engine speed - Torque - Inlet air flow - Inlet air temperature - Cooling water flow and temperatures (inlet and outlet) - Lambda sensor (wideband) <ul style="list-style-type: none"> - Educational data acquisition and control software is needed. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures’ authorization should be submitted with the tender documents. 		
1.1.3	Free and forced convection apparatus	01	
	<ul style="list-style-type: none"> - Bench mounted unit - Demonstrate the phenomena of free and forced convection and to measure temperature profiles from three different heat transfer surfaces - Vertical air duct, with a transparent front for visibility mounted on a fan at the base of the duct, three heat transfer surfaces, airflow, and temperature probes - Three heat transfer surfaces: 		

	<ul style="list-style-type: none"> ○ A flat plate surface area 0.01 - 0.02 m² ○ Pinned extended surface area 0.05 - 0.06 m² ○ Finned extended surface area 0.14 - 0.2 m² - Transparent front wall of vertical duct for the complete visualization of the process - Heat transfer surface with heater (200 - 300W) and thermocouples - Safety: Incorporated guards - K-type thermocouples for air temperature measurement - Manually adjustable airflow up to 10 m/s - Air velocity sensor, for airflow measurement - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.1.4	Heat conduction and convection apparatus	01	
	<ul style="list-style-type: none"> - Investigate heat conduction and convection using the example of a cooling fin - Cooling fin: sample heated at one end, made of metal - Samples made of different materials and different lengths - 6 fans for experiments with forced convection - Adjustable heating power and fan power - Display of temperatures, heating power and air velocity in the software - Microprocessor-based instrumentation Technical Data <ul style="list-style-type: none"> - Heater - heating power 25 - 35 W - 6x fan <ul style="list-style-type: none"> ○ Max. flow rate: 40 m³/h (Approx.) ○ Nominal speed: 14400 min⁻¹ (Approx.) - Samples, length dissipating heat <ul style="list-style-type: none"> ○ 4x approx. 100 mm (copper, aluminium, brass, steel) ○ 2x approx. 150 mm (copper, steel) - Measuring ranges <ul style="list-style-type: none"> ○ Flow velocity: 0- 10 m/s ○ Temperature: 8x 0 -325 °C ○ Heating power: 0 - 30 W - Dimensions and Weight <ul style="list-style-type: none"> ○ L x W x H: (750 – 800) x (300 – 400) x (250 – 300) mm ○ Weight: 15 - 20 kg - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		

1.1.5	Combined convection and radiation	01	
	<ul style="list-style-type: none"> - Small scale accessory - Demonstrate combined convection (free and forced) and radiation from a horizontal heated cylinder. - Consisting of a centrifugal fan with vertical outlet duct at the top of which is mounted the heated cylinder. - A heated cylinder mounted in a vertical air duct, with a fan at the base of the duct for variable air flow - Heater rating 100 Watt at 24V DC. - K-type thermocouples for air temperature upstream and surface temperature of the cylinder. - A vane type anemometer in the outlet duct for air flow rate measurement. - Comprehensive instruction manual describing how to carry out the laboratory teaching exercises in combined radiation and convection (free and forced) and their analysis as well as assembly, installation - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.1.6	Universal vibration apparatus	01	
	<p>Able to demonstrates</p> <ul style="list-style-type: none"> - Free vibrations (oscillations) in simple, compound, filar and Kater's pendulums - Centre of percussion - Free vibrations in cantilevers and a mass-spring system - Free torsional vibrations and free vibrations in beam and spring - Free and forced vibrations in a simply supported beam and a rigid beam with spring - Viscous damping - Vibration absorber <p>Products required in the apparatus,</p> <ul style="list-style-type: none"> - Free and Forced Vibrations - Free Vibrations Test Frame - Simple and Compound Pendulums - Filar Pendulums - Centre of Percussion - Free Vibrations of a Mass-Spring System and Damper Kits - Free Torsional Vibrations and Damper Kits - Free Vibrations of a Cantilever - Free Vibrations of a Beam and Spring and Damper Kit - Versatile Data Acquisition System <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the 		

	tender documents.		
1.1.7	Universal moulding machine	01	
	<p>Able to demonstrates</p> <ul style="list-style-type: none"> - Transfer and Compression Moulding of Thermosetting Plastics - Compression Moulding of Rubber compounds - Injection Moulding of Thermoplastics <p>Technical Specifications</p> <ul style="list-style-type: none"> - Clamp force - 12 tons - Shot capacity 50 - 100 ml - Machine Dimensions - 15 - 20 x 20 - 25 x 40 - 60 in - Injection Pressure- 13,500 psi - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.1.8	Balancing of reciprocating Mass	01	
	<ul style="list-style-type: none"> - Model four-cylinder engine assembly - Both primary and secondary forces and moments - Simulates one, two and four cylinder engines - Variable crank angle settings and additional piston masses – for a range of tests - Primary and secondary forces and moments in popular engine configurations - one, two and four cylinder - Primary and secondary forces and moments for different crank settings - The effect of adding additional mass to one or more pistons for any chosen crank setting - Comparing calculated forces and moments with actual results. - Electrical supply 220 V AC to 240 VAC /60 Hz - Storage temperature range: -25 °C to +55 °C - Sound Levels Less than 70 dB(A) - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product Manufactures' authorization should be submitted with the tender documents. 		
1.1.9	Optical comparator	01	
	<ul style="list-style-type: none"> - Lens turret with 3 lens capacity, Q-axis digital protractor with angular measurements to 1' resolution, 		

	<ul style="list-style-type: none"> - Non-contact measurement. - System Type: Floor Standing - Part View Orientation: Horizontal - Screen Diameter (in): 30" - X - Y Measuring Range (in): 12" -16" Optional) x 8"-10" - Motorized X-Y Axis: Standard - Focus Range (in): Approximately 3" - Work Stage (in): 25" x 9" - Angular Measurement Resolution: 1 Minute - Profile illumination: Standard - Surface illumination: Standard - Collimating Condenser with Yellow/Green filter: Standard - Lenses: 10X, 20X, 25X, 31.25X, 50X, 100X - Iris Diaphragm: Optional - Precision Rotary Vise: Optional - Vee Block on Rotary Base: Optional - Precision Fixed Vise: Optional - Precision Centers & Vees: Optional - Glass Plate Work Holder: Optional - Canopy and Curtains: Standard - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.1.10	Twin Rotor System	01	
	<ul style="list-style-type: none"> - A non-linear MIMO (Multiple Input Multiple Output) system - Phenomenological process models, Dynamics analysis - Discrete models identification, Controller design, Controller tests on the model - Controller implementation in real-time applications - Implementation of various control strategies, Data visualization. - PID controller design, testing, tuning and implementation on the model - Designed controllers are prepared in SIMULINK™ - Uses MATLAB™ control environment - Real time analysis - Specification Power requirements 200/250 V or 100/125 V, 50 or 60 Hz. - System with MATLAB™ interface card and cable - Warranty should be Minimum one year 		

	<ul style="list-style-type: none"> - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.1	Two - stage compressor test set	01	
	<ul style="list-style-type: none"> - Two independently – controlled motor driven compressors and Inter cooler and Air receiver. - It could be able to work as a single-stage, two-stage or two-stage compressor with intercooler. - Able to demonstrate the following experiments and tests: <ul style="list-style-type: none"> - Volumetric, mechanical and Isothermal efficiency - Indicated work done - Motor output power (compressor shaft power) - Pressure ratio - Temperature ratio - Inlet dryness calculations - P-V indicator diagram - Effect of inter-stage cooling on compressor total power requirements and effect on cycle temperatures - Effect of two-stage compression and inter-stage pressure on power requirements - Diverter valves to allow air to move in different directions. - Safety: Relief valves. - Digital pressure indicator is needed. - Electrical supply: 220–240 VAC, 50/60 Hz 32 A single phase - Operating temperature range: +5°C to +40°C <p>Specifications</p> <ul style="list-style-type: none"> - Speed range: 200 – 1000 rev/min - Maximum delivery pressure: 10.3 bar - Compressor: twin-cylinder, air-cooled reciprocating compressors. - Sensors for measuring torque and motor speed - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.2	Multi-pump test rig - 01	01	
	<ul style="list-style-type: none"> - A mobile self-contained multi-pump test rig, containing all the services and instrumentation for determining the characteristic curves of 8 different pumps at different speeds. - For rotodynamic pumps: <ul style="list-style-type: none"> o Pressure head vs flow o Power absorbed vs flow o Pump efficiency vs flow - For positive displacement pumps: <ul style="list-style-type: none"> o Flow vs pressure head o Power absorbed vs pressure head o Volumetric efficiency vs pressure head 		

	<ul style="list-style-type: none"> - Contains five different pump positions (4 active at the same time.) - Centrifugal pump and gear pump in standard. <p>Accessories</p> <ul style="list-style-type: none"> - Axial pump - Flexible impeller pump - Turbine pump - Diaphragm pump - Plunger pump - Additional centrifugal pump <ul style="list-style-type: none"> - A PLC control panel is for allowing the correct combination of suction, head, flow, pump speed and torque - Electronic measurement of flow, pressure head and suction head. - Optional volumetric flow measurement system for reciprocating pumps. - Optional data logging and educational software. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.3	Pelton turbine test rig	01	
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Determination of the operative characteristics of the Pelton Turbine. - Determination of the operation mechanical curves. - Determination of the operation hydraulic curves. <p>Technical Specifications</p> <ul style="list-style-type: none"> - Speed range: 0 - 2000 r.p.m. - Power: 8 - 15 W. - Manometer range: 0 - 2.5 bar. - Number of buckets: 15 - 20. - Drum radius: 25 - 35 mm. - Dynamometers range: 0 - 20 N. - Easy and quick coupling system built-in. - Anodized Aluminum structure. - Tachometer. <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.4	Axial flow turbine test rig	01	
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Flow calculation. 		

	<ul style="list-style-type: none"> - Determination of the discharge coefficient of the nozzle. - Determination of the curve $N(Q, n)$, $P(Q, n)$ and $\eta(Q, n)$; (two different nozzles). - Dimensional analysis. <p>Technical Specifications</p> <ul style="list-style-type: none"> - Nozzle: <ul style="list-style-type: none"> o Inlet diameter of the throat: 2.5 mm. o Outlet diameter of the throat: 2.5 mm. o Discharge angle: 20° and 30°. - Turbine rotor: <ul style="list-style-type: none"> o External diameter: 53 mm. o Internal diameter: 45 mm. o Number of blades: 40. o Inlet angle of the blades: 40°. o Outlet angle of the blades: 40°. o Used material: Brass. - Brake - Bourdon type manometer. - 8 ball valves. - Easy and quick coupling system built-in. - Anodized aluminum structure. - Tachometer. <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.5	Free and forced vortex apparatus	01	
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Study of forced vortex without discharge orifice. - Study of forced vortex with discharge orifice. - Study of free vortex. - Analysis of the influence of the jet inlet direction. - Analysis of the influence of the vortex on the discharge velocity <p>Technical Specifications</p> <ul style="list-style-type: none"> - Tank diameter: 300 mm (Approx.) - Tank height: 300 mm (Approx.) - Mouthpieces orifice diameters: 8, 16 and 24 mm. - Distance between centers: 0, 30, 50, 70, 90 and 110 mm. - Pitot tube with measuring points at: 15, 20, 25 and 30 mm radius and a scale. - Measurement bridge. - Inlet pipes: 9 and 12.5 mm. diameter. - Diameter measurement system by Nonius. - Blind mouthpiece with X-shaped crosses. - Easy and quick coupling system built-in. Anodized aluminum structure. - Dimensions: 600 x 550 x 1400 mm. approx. 		

	<ul style="list-style-type: none"> - Weight: 10 kg. approx <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.6	Centrifugal pumps characteristics	01	
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Obtaining of the curves H vs Q, N vs Q, Eff% vs Q of a centrifugal pump. - Making of the map of a centrifugal pump. - Representation of the dimensional curves H*, N* and rpm*. - Series coupling of two pumps of similar characteristics. - Series coupling of two pumps of different characteristics. - Parallel coupling of two pumps of similar characteristics. - Parallel coupling of two pumps of different characteristics. <p>Technical specifications</p> <ul style="list-style-type: none"> - Centrifugal pump: 0.3 - 0.4 kW, 30 - 80 l/min. at 20.1 - 12.8 m. with speed variator. - Bourdon type manometers. - Control panel for the variator, for modifying the speed, with visualization of r.p.m, power consumed on display, on/off switch. - Discharge accessory, with manometer, flow control valve and diffuser. - Vacuum meter. - Easy and quick coupling system built-in. - Anodized aluminum structure and panels of painted steel. - Dimensions: (400 – 500) x (450 – 550) x (1200 – 1300) mm. - Weight: 30 - 50 kg (Approx.) <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.7	Basic pneumatics training kit	01	
	<ul style="list-style-type: none"> - Structure, function and application of single-acting and double-acting cylinders - Calculating basic parameters of pneumatics - Direct and indirect actuation - Application and function of 3/2 and 5/2-way valves 		

	<ul style="list-style-type: none"> - Methods of actuation of directional control valves - Options for pressure measurement - Pressure-dependent control systems - Distinguishing flow control methods - Building latching circuits - Logic operations: AND/OR/NOT , limit switches, - Time delay valves - Fixed working panel (Table top) - Compressor (230 V, maximum 8 to 10 bar) Oil-lubricated, extremely quiet (45 - 50) dB - Required components: 3/2-way valve with pushbutton actuators, normally closed; 3/2-way valve with pushbutton actuators, normally open;5/2-way valve with selector switches; 3/2-way valve with selector switches, normally closed ;3/2-way roller lever valves, normally closed; Proximity sensors, pneumatic, with cylinder attachment; Pneumatic timers, normally closed; Pressure sequence valves; 3/2-way valve, pneumatically actuated at one end; 5/2-way valve, pneumatically actuated at one end; 5/2-way double pilot valve, pneumatically actuated at both ends; Shuttle valves (OR); Dual-pressure valve (AND); Quick-exhaust valves; One-way flow control valve ;Single-acting cylinders; Double-acting cylinders; Start-up valve with filter control valves; Pressure regulator valve with gauges; Pressure gauges; Manifold; Plastic tubing - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.8	Basic Electropneumatic Training Kit	01	
	<ul style="list-style-type: none"> - Structure, function and application of single-acting and double-acting cylinders - Calculating basic parameters - Direct and indirect actuation - Application and function of 3/2 and 5/2-way solenoid valves - Analyzing circuits - Options for pressure measurement - Pressure-dependent control systems - Latching circuits - Logic operations: AND/OR/NOT - Combining logic operations - Function and application of limit - Switches - Time delay valves - End-position monitoring using - electronic proximity sensors - Realizing oscillating movement - Economic considerations of using 		

	<ul style="list-style-type: none"> - pneumatic components - Troubleshooting simple electropneumatic circuits - Fixed workstation - Compressor (230 V, maximum 8 to 10 bar) Oil-lubricated, extremely quiet (45 - 50) dB - Equipment sets of individual components (cylinders, directional control valves, logic elements, time delay valves and pneumatic proximity sensors) <p>Required accessories:</p> <p>Signal inputs, electrical ;Relays, three-fold; Limit switches, electrical; Limit switch, electrical; Proximity sensor, optical; Proximity sensor, electronic, with cylinder mounting; 3/2-way solenoid valve with LED, normally closed; 5/2-way solenoid valve with LED; 5/2-way double solenoid valve with LED; Pressure sensor with display; One-way flow control valves; Single-acting cylinder; Double-acting cylinder; Start-up valve with filter control valve; Manifold; Plastic tubing</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product Manufactures' authorization should be submitted with the tender documents. 		
1.2.9	Basic Hydraulics Training Kit	01	
	<ul style="list-style-type: none"> - Design and function of pressure-relief valves, cylinders and directional control valves - Design and function of the no return valve, one-way flow control valve and piloted non-return valve - Design and function of flow control valves - Recording and interpreting the characteristic curve of a hydraulic pump - Measuring the volume flow of a hydraulic control system - Recording the characteristic curve of a pressure-relief valve - Identifying and calculating times, pressures and forces during advancing and retracting of a cylinder - Recording the characteristic curve of a flow control valve - Calculating performance ratios when using 4/3-way valves with different mid-positions <p>Hydraulic circuits:</p> <ul style="list-style-type: none"> - Commissioning hydraulic circuits safely - Using the flow control valve in the inflow and outflow and adjusting the drive speed - Difference between a flow control valve and one-way flow control valve in hydraulic control systems - Design and mode of operation of a differential circuit - Effect of the piston surfaces on pressures, forces, speeds and travel times - Proper use of piloted non-return valves - Circuits with different types of counter pressure - Operating cylinders with varying loads 		

	<p>- Fixed work panel (Table top)</p> <p>Required accessories:</p> <p>Pressure relief valves; 2-way flow control valves;</p> <p>One-way flow control valves; Non-return valve, delockable ,Non-return valve, 4/2-way hand lever valve, spring return; 4/3-way hand lever valve, relieving mid-position (AB → T), detenting;</p> <p>4/3-way hand lever valve, closed mid-position, detenting; Shut-off valves; Differential cylinders; Weights; Hydraulic motors; T-distributors; 4-way distributor with pressure gauges; Pressure gauges; Flow sensors</p> <ul style="list-style-type: none"> - Adaptable Hydraulic Power Pack - Gear motor with pressure relief valve adjustable from 0 – 6 MPa - Operating pressure Approximately 6 MPa - Motor: AC, single-phase with overload protection, start capacitor and ON/OFF switch <p>Air filter and return filter</p> <ul style="list-style-type: none"> - Low-leakage, self-sealing coupling nipples for P and T - Plug socket for unpressurised return - Connecting flange for measuring container return - Weight: 19 kg - Nominal voltage: 230 V AC - Frequency: 50 to 60 Hz - Delivery rate (rated speed): 2.2 – 2.7 l/min <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.10	PLC Trainer Kit	01	
	<ul style="list-style-type: none"> - Industrial PLC application model with programming facilities <p>Specifications:</p> <ul style="list-style-type: none"> - Main memory: Approximately 1.5 MB for program and 5 MB for data - Memory card included - Interface 1: PROFINET IRT with 2 port switches - Interface 2: Ethernet - Interface 3: PROFIBUS, 10 ns bit performance <p>Inputs/outputs:</p> <ul style="list-style-type: none"> - 32 digital inputs (24 V DC) - 32 digital outputs (24 V DC/0.5 A) - 8 x analogue inputs, 8 x U/I/RTD/TC, 16-bit resolution - 4 x analogue outputs, 4 x U/I,16-bit resolution - Integrated power supply unit, AC230 V/DC 24 V, 4.5 A - 16 digital inputs and 16 switches/pushbuttons for - Signal simulation - 16 digital outputs 4 mm safety sockets - Analogue processing 4 analogue inputs can be switched to simulation via potentiometer and 2 analogue outputs <p>Recommended accessories:</p> <ul style="list-style-type: none"> - I/O data cable - Power cables - Programming software or facility should be included 	-	

	<ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.2.11	Ball and Plate Control System	01	
	<ul style="list-style-type: none"> - Stabilizing a thrown ball onto a plate and it being stabilized exactly in the center within some seconds. - Controlled by NI LabVIEW using a NI interface card <p>Features:</p> <ul style="list-style-type: none"> - Intriguing control experiment featuring extensive courseware - Enables study of real-time control of a non-linear and unstable process - Implementation of digital control techniques using NI LabVIEW - Ball position sensing and image processing using USB camera - Open and closed loop configurations - Fully assembled plant with integral power supply <p>Practical coverage: Non-linear model testing, Plant control PID controllers, Plate orientation control, PID control of plate orientation, Real-time PID control, 1-D Ball Control, 1-D PID control of ball position, Real-time 1-D PID control of ball position, 2-D Ball Control, 2-D PID control of ball position, Real-time 2-D PID control of ball position, Trajectory tracking with ball Real-time.</p> <ul style="list-style-type: none"> - Ball & Plate Control System complete with student software, NI LabVIEW interface card and cable. <p>Specification</p> <ul style="list-style-type: none"> - Power Supply included 230 V AC - A self-contained positional control training instrument utilizing electro-magnetic actuators. - Teaching the principles of position control. - Operates in real-time when connected to a PC via a USB Operates within NI LabVIEW environment. <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.3.1	MIG welding machine	01	
	<ul style="list-style-type: none"> - DC – Lift inverter multi process welding machine - Should be able to weld the following materials <ul style="list-style-type: none"> - Steel - HSS high strength steel - Stainless steel - MIG – brazing of galvanized sheets - Aluminium - To weld on thin thickness - To modify weld seam during welding 		

	<p>Features</p> <ul style="list-style-type: none"> - Visualization on LCD display of welding parameters - Regulation of: wire speed upslope, electronic reactance, burn-back time and post gas - thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator protections <p>Accessories</p> <ul style="list-style-type: none"> - 2 MIG-MAG torches - Spool gun - Cable - Clamp <ul style="list-style-type: none"> - Complete with MIG welding accessories. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.3.2	TIG welding machine	01	
	<ul style="list-style-type: none"> - TIG, Pulse TIG and MMA inverter welding machine. - Should be able to work in direct current and alternating current. - Should be able to weld the following materials <ul style="list-style-type: none"> - Steel - Stainless steel - Titanium - Copper - Magnesium - Aluminium - Alloys of above materials <p>Characteristics</p> <p>Pulse and EASY pulse operation</p> <ul style="list-style-type: none"> - Adjustable pre-heating for simpler striking in AC - TIG regulations: bi-level, startup/end current, spot welding time, pre/post gas, current up/down slope, balance DC / AC, square wave frequency - THINSPOT function for quick and precise tack welding - MMA regulations: arc force and hot start - Anti-stick device - VRD device - Remote control connector - Thermostatic, overvoltage, undervoltage, overcurrent protections. <ul style="list-style-type: none"> - Complete with TIG welding accessories. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		

1.3.3	Metallography specimen grinding & polishing machine	01	
	<ul style="list-style-type: none"> - Metallography specimen preparing for micro structure analysis <p>Main features:</p> <ul style="list-style-type: none"> - Stainless steel parts for rust protection - Double working disks. - Working disk can be changed and replaced swiftly - Step less speed changing status or two-level constant speed status. - Working condition can be switched from one to another easily. - Selection option for rotating direction of working disk <p>Technical specifications:</p> <ul style="list-style-type: none"> - Rotating speed of working disk: 50-600rpm (step less speed changing) - Diameter of working disk: Approximately 300mm - Power supply: 220V 50Hz <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.3.4	Hot Metal Press Machine	01	
	<p>Metallurgy preparation includes uniform size and shape in order hot mounting (hot compression mounting) is ideal.</p> <ul style="list-style-type: none"> - Operates on electro hydraulic pressure. - HMI LCD display - Quick interchangeable mould cylinders for desired sizes. - Parameters preloaded for quick selection. - Fully automatic - Intermediate ram included for dual mounts - Robust bayonet - Corrosion resistant steel - Cycle completion alarm notification - Temperature up to 300° C - Pressure up to 350 Bars (5000 psi) - Mould Sizes 25mm,30mm,40mm,50mm - Electrical supply: 240V, 1-phase, 50/60 Hz <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.3.5	Sheet Metal Arc Welding	01	
	<p>MMA (Manual Metal Arc) stick electrode welding machine in alternating current (AC).</p> <p>Main Features:</p> <ul style="list-style-type: none"> - Step less regulation of welding current. - Thermostatic protection. - Use with a wide range of electrodes: rutile. 		

	<ul style="list-style-type: none"> - Complete with MMA welding accessories including mask. - Dual voltage power supply. - Fit with accessories and wheels - Step less current adjustment - 230 V single phase , 50/60 Hz - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 		
1.4.1	MARSHALL STABILITY AND FLOW	01	
	<p>Load frame</p> <ul style="list-style-type: none"> - Geared screw jack and motor drive - System should have internal limit switch for both directions of travel. - mechanical load frame should be bench mounted and constructed to encompass the Strain and loads involved with the test. - at least 50 kN capacity - Platen speed 50.8 mm per minute - Weight: 65 - 70 kg (total system) - Dimensions (l x w x h): max. 550 x 400 x 870 mm - Power requirements: 220-240 V AC, 50-60 Hz, 1 ph <p>Flow Meter – (02 nos.)</p> <ul style="list-style-type: none"> - Dial gauge graduated 0.01 mm with 25 mm travel. - Supplied with stem brake unit and flow meter pedestal. <p>Breaking Head (Marshall)</p> <ul style="list-style-type: none"> - complete with gauge disc - weight 9 kg <p>Load Measuring Ring 50 kN</p> <ul style="list-style-type: none"> - Should be calibrated in compression <p>Load Measuring Ring 25 kN</p> <ul style="list-style-type: none"> - Should be calibrated in compression <p>Electronic Control and Readout Unit</p> <ul style="list-style-type: none"> - Can be programmed to automatically stop the load frame when transducer limits exceed, protecting test accessories and load frame drive system - To record Peak load and the corresponding flow - software supporting Windows 7 or above to download results - SI Units - Large character LCD display <p>S - type Load Cell</p> <ul style="list-style-type: none"> - 50 kN capacity <p>Flow Transducer</p> <ul style="list-style-type: none"> - Pre-calibrated, for use with Breaking Head 		
	<p>Documentation</p> <p>All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p>		

	Warranty : Minimum three years		
1.4.2	WATER BATH TO KEEP ASPHALT SPECIMENS BEFORE MARSHALL TEST	01	
	<ul style="list-style-type: none"> - Capacity - 60 L - LED display - Cover and internal perforated shelf - Temperature range: Ambient to 95°C ± 1°C (controllable) - Power requirements : 220 – 240 V AC, 50 – 60 Hz 1 ph 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum one year</p>		
1.4.3	ASPHALT MIX COMPACTION MOULD AND ACCESSORIES	03	
	<p>Compaction Mould – 03 Nos.</p> <ul style="list-style-type: none"> - mould body - baseplate - Combined filling/extraction collar - Weight: 3.5 kg <p>Compaction Hammer – 03 Nos.</p> <ul style="list-style-type: none"> - Should satisfy BS 598 - The hammer has a 4535 g sliding weight with a free fall of 457 mm - total Weight: 7.85 kg <p>Compaction Pedestal</p> <ul style="list-style-type: none"> - Should satisfy BS 598 - 300 mm sq x 25 mm thick steel plate complete with 4 tie rods and securing nuts. - A mould clamp and hammer guide are fitted to the plate - Supplied complete with a laminated hardwood block. - Weight 35 - 45 kg <p>Paper Discs (Pack of 100)</p> <ul style="list-style-type: none"> - Non-absorbent, 99 mm diameter <p>Steel Block (To heat the compaction hammer foot)</p> <ul style="list-style-type: none"> - 100 mm diameter x 50 mm height. - Weight max. 3 kg. <p>Spatula (200 mm) – 03 nos.</p>		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum One year</p>		

1.4.4	RING AND BALL APPARATUS AND ACCESSORIES	01	
	<p>Ring and Ball Apparatus</p> <ul style="list-style-type: none"> - System should be with 2 shouldered pattern rings, 2 ball-centering guides and 2 balls - The support frame of the apparatus should be retained in a heat resistant container - Weight of the system : 550 - 600 g <p>Magnetic stirrer</p> <ul style="list-style-type: none"> - Stirrer should provide fine temperature control of liquid up to a maximum temperature of +150°C. - And should be with variable stirring speed options. - Weight max. 2 kg - Power requirements: 220 – 240 V AC, 50 - 60 Hz, 1 ph <p>Thermometer</p> <ul style="list-style-type: none"> - should offer a thermometer with range suitable for the system 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>		
1.4.5	PENETRATION TEST AND ACCESSORIES	01	
	<p>Standard Penetrometer</p> <ul style="list-style-type: none"> - The 150 mm diameter dial should be graduated in 400 divisions of 0.1 mm <p>Semi-automatic Penetrometer</p> <ul style="list-style-type: none"> - Should be incorporated digital Automatic Controller which releases the needle assembly, - The time set should be displayed by a bright, easy to read display. - Weight 8 - 10 kg - Power requirement: 220 – 240 V AC, 50 – 60 Hz, 1 ph. <p>Penetration Needle.</p> <ul style="list-style-type: none"> - Hardened steel, should be supplied with verification certificate - Weight 2.5 g <p>Constant Temperature Bath.</p> <ul style="list-style-type: none"> - A bench mounting bath should be offered specially designed for the conditioning of bitumen samples prior to penetration tests. Must be incorporated with a highly accurate thermostat, the bath should be able to maintain a temperature between 20 and 70°C ± 0.1°C. - Weight 18.2 kg - Power requirements: 220 – 240 V AC, 50 Hz, 1 ph. <p>Transfer Dish should be offered</p> <p>Penetration Tin (For penetrations between 200 and 350) – 03 Nos.</p> <ul style="list-style-type: none"> - Approximately 70 mm diameter x 45 mm deep. - Weight 25 - 35 g <p>Penetration Tin (for penetrations below 200) – 03 Nos.</p> <ul style="list-style-type: none"> - Approximately 55 mm diameter x 35 mm deep. - Weight 20 - 30 g 		

	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum one year</p>		
1.4.6	DUCTILITY TESTING MACHINE (ELECTRICALLY OPERATED)	01	
	<ul style="list-style-type: none"> - Must be able to test at least test three specimens simultaneously. - The electric motor driven reduction gear unit must be smooth constant speed on continuous operational conditions. - The system must be mounted with water bath - Completely encased in metal bound hardwood. - The temperature controller must be a digital 63ontroller - Atleast two rates of travel must be provided. - The machine to be supplied complete with 4 ductility molds (Briquette mould), each with a base plate. - Should satisfy ASTM D 113, AASHTO T51standards. 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum two years</p>		
1.5.1	PROCTOR COMPACTION MOULD AND RAMMER	03	
	<p>Mould</p> <ul style="list-style-type: none"> - Dimensions (dia. X height) : 101.6 x 116.4 mm - Rammer Mould volume : 1/30 ft³ - Construction : All steel, threaded studs with wing nuts, plated - Weight : 5.4 kg <p>Rammer</p> <ul style="list-style-type: none"> - Rammer : 50 mm dia, 2.5 kg - Drop : 300 mm - Guide sleeve : Machined steel tubing with air pressure release holes - Finish : Corrosion resistant - Weight : 4.1 kg <p>Rammer</p> <ul style="list-style-type: none"> - Rammer : 50 mm dia, 4.5 kg - Drop : 450 mm - Guide sleeve : Machined steel tubing with air pressure release holes - Finish : Corrosion resistant - Weight : 7.5 kg <p>Straight edge, 300 mm</p>		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum one year</p>		

1.5.2	CBR TEST MACHINE	01	
	<p>Load frame</p> <ul style="list-style-type: none"> - 50 kN load frame complete with stabilising bar. - Must be a two speed machine [covering BS (1.00 mm/min) and ASTM (1.27 mm/min) standards] - Rapid platen adjustment must be available. - Must be a Compact, bench-mounting design. - Options for mechanical or electronic measurement must be available. - Close control of application of a seating load must be available. - Dimensions (l x w x h): 550 x 400 x 1220 mm - Maximum vertical clearance : 800 mm - Horizontal clearance : 255 mm - Platen diameter : 133 mm - Platen travel : 105 mm - Weight : 75 - 85 kg - Power requirements: 220 V AC, 50 Hz, 1ph 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum three years</p>		
1.5.3	CBR MOULD AND ACCESSORIES	03	
	<p>CBR Mould with collar and perforated Baseplate.</p> <ul style="list-style-type: none"> - Mould (inside dia. x height): 152 x 127 mm - Collar : 51 mm height, fits both ends of mould Base plate: Solid, fits both ends of mould - Construction : All steel, plated - Weight : 7.3 kg <p>CBR Perforated Base Plate to fit mould body. CBR Cutting Collar to fit mould body C-spanner to fit CBR moulds and Collars Base Plate Tool to fit into base plate to assist removal from mould body. Static Compaction Plug.</p> <ul style="list-style-type: none"> - Steel, 150 mm dia x 51 mm thick. Complete with removable handle. <p>2 kg Annular Surcharge Weigh 2 kg Split Surcharge Weight Tamping Rod Swell Plate with adjustable stem Swell Tripod for mounting Swell Dial Gauge in position on CBR mould collar Soaking Tank Swell Dial Gauge</p> <ul style="list-style-type: none"> - (25 mm travel x 0.01 mm divisions) <p>Filter Papers: Box of 100 Nos</p> <ul style="list-style-type: none"> - 150 mm diameter <p>Penetration Piston</p> <ul style="list-style-type: none"> - 1.935 mm² area foot of case hardened steel. - Weight 3.7 kg. 		

	<p>Penetration Dial Gauge</p> <ul style="list-style-type: none"> - 25 mm travel (0.01 mm divisions) - Complete with rack extensions and chisel edge anvil - Weight 220 g <p>Mounting bracket for CBR penetration dial gauges</p> <ul style="list-style-type: none"> - To fix gauges to penetration piston or load ring. 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available Warranty : Minimum one year</p>		
1.5.4	DYNAMIC CONE PENETROMETER	02	
	<ul style="list-style-type: none"> - To be supplied with all necessary tools, assembly and operating instructions - Assembled height 1965 mm - Assembled weight 20 kg - an 8 kg weight with a drop of 575 mm, - a 20 mm diameter cone fitted to the end of the shaft - To be used for rapid in-situ measurement of the structural properties of existing road pavement constructed with unbound materials - should be supplied with a Replacement Cone 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available Warranty : Minimum one year</p>		
1.5.5	CASAGRANDE LIQUID LIMIT DEVICE WITH COUNTER	01	
	<ul style="list-style-type: none"> - Satisfy BS/EN Standard - Supplied with metal grooving tool & test gauge 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available Warranty : Minimum one year</p>		
1.5.6	LINEAR SHRINKAGE MOULD	06	
	<ul style="list-style-type: none"> - Satisfy BS 1377 Standard - To produce a specimen 140 mm long x 12.5 mm radius. 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available Warranty : Minimum one year</p>		

1.5.7	SAMPLE EJECTOR		01
	<ul style="list-style-type: none"> - Dimensions (w x d x h, inches): max. 10-1/2 x 8 x 22-1/2 - Capacity: 2” and 3” Shelby tubes up to 7”; 4” and 6” molds. - Pushing Force max. 6,000 lbf - Jack Hydraulic; hand-operated; 7” stroke - Construction: All metal; plated extrusion plates and piston discs; painted finish on housing and pump - Weight : 25 – 30 kg - To be supplied with 2” – 6” ejector heads and adapter plates 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>		
1.5.8	Traixal Machine Accessories-CU/CD System (ELE, EL25-4047)		01
	<ul style="list-style-type: none"> • De-Aired Water Appartus. 15 L Cap. 220-240V 50/60Hz 1Ph – 01 • Piston Restraint Clamp for Ele Triaxial Cells Manufactured from July 1996 – 1 No • Valve No Volume Change ¼ inch BSp Fitted with 6 mm Connector and Integral Sealing Ring – 1 No • Two –way split former 100 mm diameter – 1No • Porous disc 100mm Diameter Pack of 2 – 1 No • Filter Paper drain 100mm/4 inch diameter. Pack of 50 – 1 No • Pressure test 1700 Oil/Water constant pressure system 0 to 1700Kpa 220-240V 50/60Hz 1Ph. – 2 Nos • Digital Pressure Gauge 1700Kpa for use with 26-1800 series Oil/Water constant pressure system – 1 No • Red dye Kerosene soluble 10G Phial for Colouring Kerosene – 1 No • Digital Pressure Gauge 1700Kpa. For Ele Triaxial Cells. – 1 No 		
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>		
1.5.9	Motorized Pendulum Impact Testing System		01
	Impact Energy	300-900 Joule	
	Release Angle (adjustable)	150°	
	Pendulum Length	750 - 770 mm	
	Maximum Hammer Speed	5.0 – 5.5 m/s	
	Encoder Resolution	0.036°	
	System Dimensions(W x D x H)	2200 x 1117 x 1990mm	
	Net Weight	1200 – 1300 kg	
	Power	230 Vac, 1 Phase, 50/60 Hz, 15 Amp	

	Should meet the following standards • ASTM E23 • ISO 148 • EN 10045 • GOST 9454 • AS 1544 • JIS Z 2242 • JIS B 7722		
	Automatic test start at door closure		
	Optional interchangeable hammer weights		
	Safety enclosure with interlocks		
	Data Acquisition Software Specification (English version)		
	Calculations	Energy absorbed and Elasticity/Resilience	
	Data Collection Rate	1 kHz	
	Reporting Capability	Stores results as .csv files that can opened in applications such as Microsoft Excel and Ability to define 10 user-designed input fields	
	Simple System Setup	Hammer characteristics on single setup page and Setup parameters stored to device	
	Display Features	Status of System limits, Hammer setup and verification, Potential/impact energy, velocity and test history and Modulus of Elasticity	
	Package Includes	Angular encoder, USB communication box, Mounting hardware and inter-connect cables and Network connectivity	
	Documentation	All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product	
	Warranty	Minimum three years	
1.5.10	Moisture Can		100
	Aluminium, 75x25mm with lids		
1.5.11	Concrete Cube Mould		25
	Size - 150x150x150mm, 4-Part Clamp Type / 2-Part (L-Shape) Cast Iron		
1.5.12	Cube Mould Tamping Bar		5
	25mm square face, Steel		

3. Bidders Response

Item No	Name and Minimum Specifications	Bidder's Response		If "No" indicate the specification Offered
		Yes	No	
1.1.1	Automotive diesel engine			
	<ul style="list-style-type: none"> - A 4-cylinder, water cooled, Biodiesel compatible, diesel engine - Variable load eddy current dynamometer - Strong steel framework support - Computer controlled starter, throttle and dynamometer. - Engine indicator for measuring cylinder pressure - Electrical supply: 220-240V, single phase - Cooling water supply: 6 - 8 l/min at 3 bar pressure - Safety: <ul style="list-style-type: none"> - Guard protection for moving parts. - Safety interlocks - Emergency stops <p>Technical specifications</p> <p>Engine data:</p> <p>Engine Model</p> <ul style="list-style-type: none"> - Power (45 – 50) kW - Displacement: 1850cc – 1900cc - Bore: 75 - 80 mm - Stroke: 90 - 100 mm - Cylinders: 4 <p>Dynamometer data:</p> <ul style="list-style-type: none"> - Dynamometer type: Eddy Current - Cooling: Air cooled <p>Instrumentation and sensors:</p> <ul style="list-style-type: none"> - Engine speed - Torque - Inlet air flow - Inlet air temperature - Cooling water flow and temperatures (inlet and outlet) <ul style="list-style-type: none"> - Educational data acquisition and control software is needed. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			

1.1.2	Gasoline engine			
	<ul style="list-style-type: none"> - High efficiency, three cylinder, water cooled, normally aspirated engine - Biofuel Compatible. - Variable load, eddy current dynamometer - Ignition and Injection Control system - Strong steel framework support - Remotely controlled throttle and brake load. - Engine Indicator set for production of real time P-V diagram. - Electrical supply: 220-240V, single phase - Cooling water supply: 6 - 8 l/min at 3 bar pressure - Safety: <ul style="list-style-type: none"> - Guard protection for moving parts. - Safety interlocks - Emergency stops <p>Technical specifications</p> <p>Engine data:</p> <ul style="list-style-type: none"> - Power (35 – 45) kW - Displacement: 1190cc – 1200cc - Bore: 75 – 80 mm - Stroke: 85 - 90 mm - Cylinders: 3 (6 valve) <p>Dynamometer data</p> <ul style="list-style-type: none"> - Dynamometer type: Eddy Current - Cooling: Air cooled <p>Instrumentation and sensors</p> <ul style="list-style-type: none"> - Engine speed - Torque - Inlet air flow - Inlet air temperature - Cooling water flow and temperatures (inlet and outlet) - Lambda sensor (wideband) <ul style="list-style-type: none"> - Educational data acquisition and control software is needed. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufacturers' authorization should be submitted with the tender documents. 			

1.1.3	Free and forced convection apparatus			
	<ul style="list-style-type: none"> - Bench mounted unit - Demonstrate the phenomena of free and forced convection and to measure temperature profiles from three different heat transfer surfaces - Vertical air duct, with a transparent front for visibility mounted on a fan at the base of the duct, three heat transfer surfaces, airflow, and temperature probes - Three heat transfer surfaces: <ul style="list-style-type: none"> o A flat plate surface area 0.01 - 0.02 m² o Pinned extended surface area 0.05 - 0.06 m² o Finned extended surface area 0.14 - 0.2 m² - Transparent front wall of vertical duct for the complete visualization of the process - Heat transfer surface with heater (200 - 300W) and thermocouples - Safety: Incorporated guards - K-type thermocouples for air temperature measurement - Manually adjustable airflow up to 10 m/s - Air velocity sensor, for airflow measurement - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.1.4	Heat conduction and convection apparatus			
	<ul style="list-style-type: none"> - Investigate heat conduction and convection using the example of a cooling fin - Cooling fin: sample heated at one end, made of metal - Samples made of different materials and different lengths - 6 fans for experiments with forced convection - Adjustable heating power and fan power - Display of temperatures, heating power and air velocity in the software - Microprocessor-based instrumentation <p>Technical Data</p> <ul style="list-style-type: none"> - Heater - heating power 25 - 35 W - 6x fan <ul style="list-style-type: none"> o Max. flow rate: 40 m³/h (Approx.) o Nominal speed: 14400 min⁻¹ (Approx.) - Samples, length dissipating heat <ul style="list-style-type: none"> o 4x approx. 100 mm (copper, aluminium, brass, steel) o 2x approx. 150 mm (copper, steel) - Measuring ranges <ul style="list-style-type: none"> o Flow velocity: 0- 10 m/s o Temperature: 8x 0 -325 °C o Heating power: 0 - 30 W 			

	<ul style="list-style-type: none"> - Dimensions and Weight <ul style="list-style-type: none"> o L x W x H: (750 – 800) x (300 – 400) x (250 – 300) mm o Weight: 15 - 20 kg - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.1.5	Combined convection and radiation			
	<ul style="list-style-type: none"> - Small scale accessory - Demonstrate combined convection (free and forced) and radiation from a horizontal heated cylinder. - Consisting of a centrifugal fan with vertical outlet duct at the top of which is mounted the heated cylinder. - A heated cylinder mounted in a vertical air duct, with a fan at the base of the duct for variable air flow - Heater rating 100 Watt at 24V DC. - K-type thermocouples for air temperature upstream and surface temperature of the cylinder. - A vane type anemometer in the outlet duct for air flow rate measurement. - Comprehensive instruction manual describing how to carry out the laboratory teaching exercises in combined radiation and convection (free and forced) and their analysis as well as assembly, installation - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.1.6	Universal vibration apparatus			
	<p>Able to demonstrates</p> <ul style="list-style-type: none"> - Free vibrations (oscillations) in simple, compound, filar and Kater's pendulums - Centre of percussion - Free vibrations in cantilevers and a mass-spring system - Free torsional vibrations and free vibrations in beam and spring - Free and forced vibrations in a simply supported beam and a rigid beam with spring - Viscous damping - Vibration absorber <p>Products required in the apparatus,</p> <ul style="list-style-type: none"> - Free and Forced Vibrations - Free Vibrations Test Frame - Simple and Compound Pendulums 			

	<ul style="list-style-type: none"> - Filar Pendulums - Centre of Percussion - Free Vibrations of a Mass-Spring System and Damper Kits - Free Torsional Vibrations and Damper Kits - Free Vibrations of a Cantilever - Free Vibrations of a Beam and Spring and Damper Kit - Versatile Data Acquisition System <p>- Warranty should be Minimum one year</p> <p>- All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents.</p>			
1.1.7	Universal moulding machine			
	<p>Able to demonstrates</p> <ul style="list-style-type: none"> - Transfer and Compression Moulding of Thermosetting Plastics - Compression Moulding of Rubber compounds - Injection Moulding of Thermoplastics <p>Technical Specifications</p> <ul style="list-style-type: none"> - Clamp force - 12 tons - Shot capacity 50 - 100 ml - Machine Dimensions - 15 - 20 x 20 - 25 x 40 - 60 in - Injection Pressure- 13,500 psi <p>- Warranty should be Minimum one year</p> <p>- All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents.</p>			
1.1.8	Balancing of reciprocating Mass			
	<ul style="list-style-type: none"> - Model four-cylinder engine assembly - Both primary and secondary forces and moments - Simulates one, two and four cylinder engines - Variable crank angle settings and additional piston masses – for a range of tests - Primary and secondary forces and moments in popular engine configurations - one, two and four cylinder - Primary and secondary forces and moments for different crank settings - The effect of adding additional mass to one or more pistons for any chosen crank setting - Comparing calculated forces and moments with actual results. - Electrical supply 220 V AC to 240 VAC /60 Hz - Storage temperature range: -25 °C to +55 °C 			

	<ul style="list-style-type: none"> - Sound Levels Less than 70 dB(A) - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product Manufactures' authorization should be submitted with the tender documents. 			
1.1.9	Optical comparator			
	<ul style="list-style-type: none"> - Lens turret with 3 lens capacity, Q-axis digital protractor with angular measurements to 1' resolution, - Non-contact measurement. - System Type: Floor Standing - Part View Orientation: Horizontal - Screen Diameter (in): 30" - X - Y Measuring Range (in): 12" -16" Optional) x 8"-10" - Motorized X-Y Axis: Standard - Focus Range (in): Approximately 3" - Work Stage (in): 25" x 9" - Angular Measurement Resolution: 1 Minute - Profile illumination: Standard - Surface illumination: Standard - Collimating Condenser with Yellow/Green filter: Standard - Lenses: 10X, 20X, 25X, 31.25X, 50X, 100X - Iris Diaphragm: Optional - Precision Rotary Vise: Optional - Vee Block on Rotary Base: Optional - Precision Fixed Vise: Optional - Precision Centers & Vees: Optional - Glass Plate Work Holder: Optional - Canopy and Curtains: Standard - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			

1.1.10	Twin Rotor System			
	<ul style="list-style-type: none"> - A non-linear MIMO (Multiple Input Multiple Output) system - Phenomenological process models, Dynamics analysis - Discrete models identification, Controller design, Controller tests on the model - Controller implementation in real-time applications - Implementation of various control strategies, Data visualization. - PID controller design, testing, tuning and implementation on the model - Designed controllers are prepared in SIMULINK™ - Uses MATLAB™ control environment - Real time analysis - Specification Power requirements 200/250 V or 100/125 V, 50 or 60 Hz. - System with MATLAB™ interface card and cable - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.1	Two - stage compressor test set			
	<ul style="list-style-type: none"> - Two independently – controlled motor driven compressors and Inter cooler and Air receiver. - It could be able to work as a single-stage, two-stage or two-stage compressor with intercooler. - Able to demonstrate the following experiments and tests: <ul style="list-style-type: none"> - Volumetric, mechanical and Isothermal efficiency - Indicated work done - Motor output power (compressor shaft power) - Pressure ratio - Temperature ratio - Inlet dryness calculations - P-V indicator diagram - Effect of inter-stage cooling on compressor total power requirements and effect on cycle temperatures - Effect of two-stage compression and inter-stage pressure on power requirements - Diverter valves to allow air to move in different directions. - Safety: Relief valves. - Digital pressure indicator is needed. - Electrical supply: 220–240 VAC, 50/60 Hz 32 A single phase - Operating temperature range: +5°C to +40°C <p>Specifications</p> <ul style="list-style-type: none"> - Speed range: 200 – 1000 rev/min 			

	<ul style="list-style-type: none"> - Maximum delivery pressure: 10.3 bar - Compressor: twin-cylinder, air-cooled reciprocating compressors. - Sensors for measuring torque and motor speed - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.2	Multi-pump test rig - 01			
	<ul style="list-style-type: none"> - A mobile self-contained multi-pump test rig, containing all the services and instrumentation for determining the characteristic curves of 8 different pumps at different speeds. - For rotodynamic pumps: <ul style="list-style-type: none"> o Pressure head vs flow o Power absorbed vs flow o Pump efficiency vs flow - For positive displacement pumps: <ul style="list-style-type: none"> o Flow vs pressure head o Power absorbed vs pressure head o Volumetric efficiency vs pressure head - Contains five different pump positions (4 active at the same time.) - Centrifugal pump and gear pump in standard. <p>Accessories</p> <ul style="list-style-type: none"> - Axial pump - Flexible impeller pump - Turbine pump - Diaphragm pump - Plunger pump - Additional centrifugal pump - A PLC control panel is for allowing the correct combination of suction, head, flow, pump speed and torque - Electronic measurement of flow, pressure head and suction head. - Optional volumetric flow measurement system for reciprocating pumps. - Optional data logging and educational software. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.3	Pelton turbine test rig			
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Determination of the operative characteristics of the Pelton Turbine. 			

	<ul style="list-style-type: none"> - Determination of the operation mechanical curves. - Determination of the operation hydraulic curves. <p>Technical Specifications</p> <ul style="list-style-type: none"> - Speed range: 0 - 2000 r.p.m. - Power: 8 - 15 W. - Manometer range: 0 - 2.5 bar. - Number of buckets: 15 - 20. - Drum radius: 25 - 35 mm. - Dynamometers range: 0 - 20 N. - Easy and quick coupling system built-in. - Anodized Aluminum structure. - Tachometer. <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.4	Axial flow turbine test rig			
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Flow calculation. - Determination of the discharge coefficient of the nozzle. - Determination of the curve $N(Q, n)$, $P(Q, n)$ and $\eta(Q, n)$; (two different nozzles). - Dimensional analysis. <p>Technical Specifications</p> <ul style="list-style-type: none"> - Nozzle: <ul style="list-style-type: none"> o Inlet diameter of the throat: 2.5 mm. o Outlet diameter of the throat: 2.5 mm. o Discharge angle: 20° and 30°. - Turbine rotor: <ul style="list-style-type: none"> o External diameter: 53 mm. o Internal diameter: 45 mm. o Number of blades: 40. o Inlet angle of the blades: 40°. o Outlet angle of the blades: 40°. o Used material: Brass. - Brake - Bourdon type manometer. - 8 ball valves. - Easy and quick coupling system built-in. - Anodized aluminum structure. - Tachometer. <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with 			

	<p>Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents.</p>			
1.2.5	Free and forced vortex apparatus			
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Study of forced vortex without discharge orifice. - Study of forced vortex with discharge orifice. - Study of free vortex. - Analysis of the influence of the jet inlet direction. - Analysis of the influence of the vortex on the discharge velocity <p>Technical Specifications</p> <ul style="list-style-type: none"> - Tank diameter: 300 mm (Approx.) - Tank height: 300 mm (Approx.) - Mouthpieces orifice diameters: 8, 16 and 24 mm. - Distance between centers: 0, 30, 50, 70, 90 and 110 mm. - Pitot tube with measuring points at: 15, 20, 25 and 30 mm radius and a scale. - Measurement bridge. - Inlet pipes: 9 and 12.5 mm. diameter. - Diameter measurement system by Nonius. - Blind mouthpiece with X-shaped crosses. - Easy and quick coupling system built-in. Anodized aluminum structure. - Dimensions: 600 x 550 x 1400 mm. approx. - Weight: 10 kg. approx <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.6	Centrifugal pumps characteristics			
	<p>Able to demonstrates,</p> <ul style="list-style-type: none"> - Obtaining of the curves H vs Q, N vs Q, Eff% vs Q of a centrifugal pump. - Making of the map of a centrifugal pump. - Representation of the dimensional curves H*, N* and rpm*. - Series coupling of two pumps of similar characteristics. - Series coupling of two pumps of different characteristics. - Parallel coupling of two pumps of similar characteristics. 			

	<ul style="list-style-type: none"> - Parallel coupling of two pumps of different characteristics. <p>Technical specifications</p> <ul style="list-style-type: none"> - Centrifugal pump: 0.3 - 0.4 kW, 30 - 80 l/min. at 20.1 - 12.8 m. with speed variator. - Bourdon type manometers. - Control panel for the variator, for modifying the speed, with visualization of r.p.m, power consumed on display, on/off switch. - Discharge accessory, with manometer, flow control valve and diffuser. - Vacuum meter. - Easy and quick coupling system built-in. - Anodized aluminum structure and panels of painted steel. - Dimensions: (400 – 500) x (450 – 550) x (1200 – 1300) mm. - Weight: 30 - 50 kg (Approx.) <p>Should be compatible with existing hydraulic bench (Base Service Unit: FME00. Hydraulics Bench)</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.7	Basic pneumatics training kit			
	<ul style="list-style-type: none"> - Structure, function and application of single-acting and double-acting cylinders - Calculating basic parameters of pneumatics - Direct and indirect actuation - Application and function of 3/2 and 5/2-way valves - Methods of actuation of directional control valves - Options for pressure measurement - Pressure-dependent control systems - Distinguishing flow control methods - Building latching circuits - Logic operations: AND/OR/NOT , limit switches, - Time delay valves - Fixed working panel (Table top) - Compressor (230 V, maximum 8 to 10 bar) Oil-lubricated, extremely quiet (45 - 50) dB - Required components: <p>3/2-way valve with pushbutton actuators, normally closed; 3/2-way valve with pushbutton actuators, normally open; 5/2-way valve with selector switches; 3/2-way valve with selector switches, normally closed ; 3/2-way roller lever valves, normally closed; Proximity sensors, pneumatic, with cylinder attachment; Pneumatic timers, normally closed; Pressure sequence valves; 3/2-way valve, pneumatically</p>			

	<p>actuated at one end; 5/2-way valve, pneumatically actuated at one end;</p> <p>5/2-way double pilot valve, pneumatically actuated at both ends; Shuttle valves (OR); Dual-pressure valve (AND); Quick-exhaust valves; One-way flow control valve ;Single-acting cylinders; Double-acting cylinders;</p> <p>Start-up valve with filter control valves; Pressure regulator valve with gauges; Pressure gauges; Manifold; Plastic tubing</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.8	Basic Electropneumatic Training Kit			
	<ul style="list-style-type: none"> - Structure, function and application of single-acting and double-acting cylinders - Calculating basic parameters - Direct and indirect actuation - Application and function of 3/2 and 5/2-way solenoid valves - Analyzing circuits - Options for pressure measurement - Pressure-dependent control systems - Latching circuits - Logic operations: AND/OR/NOT - Combining logic operations - Function and application of limit - Switches - Time delay valves - End-position monitoring using - electronic proximity sensors - Realizing oscillating movement - Economic considerations of using - pneumatic components - Troubleshooting simple electropneumatic circuits - Fixed workstation - Compressor (230 V, maximum 8 to 10 bar) Oil-lubricated, extremely quiet (45 - 50) dB - Equipment sets of individual components (cylinders, directional control valves, logic elements, time delay valves and pneumatic proximity sensors) <p>Required accessories:</p> <p>Signal inputs, electrical ;Relays, three-fold; Limit switches, electrical; Limit switch, electrical; Proximity sensor, optical; Proximity sensor, electronic, with cylinder mounting; 3/2-way solenoid valve with LED, normally closed; 5/2-way solenoid valve with LED; 5/2-way double solenoid valve with LED; Pressure sensor with display; One-way flow</p>			

	<p>control valves; Single-acting cylinder; Double-acting cylinder; Start-up valve with filter control valve; Manifold; Plastic tubing</p> <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product Manufacturers' authorization should be submitted with the tender documents. 			
1.2.9	Basic Hydraulics Training Kit			
	<ul style="list-style-type: none"> - Design and function of pressure-relief valves, cylinders and directional control valves - Design and function of the no return valve, one-way flow control valve and piloted non-return valve - Design and function of flow control valves - Recording and interpreting the characteristic curve of a hydraulic pump - Measuring the volume flow of a hydraulic control system - Recording the characteristic curve of a pressure-relief valve - Identifying and calculating times, pressures and forces during advancing and retracting of a cylinder - Recording the characteristic curve of a flow control valve - Calculating performance ratios when using 4/3-way valves with different mid-positions <p>Hydraulic circuits:</p> <ul style="list-style-type: none"> - Commissioning hydraulic circuits safely - Using the flow control valve in the inflow and outflow and adjusting the drive speed - Difference between a flow control valve and one-way flow control valve in hydraulic control systems - Design and mode of operation of a differential circuit - Effect of the piston surfaces on pressures, forces, speeds and travel times - Proper use of piloted non-return valves - Circuits with different types of counter pressure - Operating cylinders with varying loads - Fixed work panel (Table top) <p>Required accessories:</p> <p>Pressure relief valves; 2-way flow control valves; One-way flow control valves; Non-return valve, delockable ,Non-return valve, 4/2-way hand lever valve, spring return; 4/3-way hand lever valve, relieving mid-position (AB -> T), detenting;</p> <p>4/3-way hand lever valve, closed mid-position, detenting; Shut-off valves; Differential cylinders; Weights; Hydraulic motors; T-distributors; 4-way distributor with pressure gauges; Pressure gauges; Flow sensors</p> <ul style="list-style-type: none"> - Adaptable Hydraulic Power Pack - Gear motor with pressure relief valve adjustable from 0 – 6 MPa 			

	<ul style="list-style-type: none"> - Operating pressure Approximately 6 MPa - Motor: AC, single-phase with overload protection, start capacitor and ON/OFF switch - Air filter and return filter - Low-leakage, self-sealing coupling nipples for P and T - Plug socket for unpressurised return - Connecting flange for measuring container return - Weight: 19 kg - Nominal voltage: 230 V AC - Frequency: 50 to 60 Hz - Delivery rate (rated speed): 2.2 – 2.7 l/min - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.2.10	PLC Trainer Kit			
	<ul style="list-style-type: none"> - Industrial PLC application model with programming facilities <p>Specifications:</p> <ul style="list-style-type: none"> - Main memory: Approximately 1.5 MB for program and 5 MB for data - Memory card included - Interface 1: PROFINET IRT with 2 port switches - Interface 2: Ethernet - Interface 3: PROFIBUS, 10 ns bit performance <p>Inputs/outputs:</p> <ul style="list-style-type: none"> - 32 digital inputs (24 V DC) - 32 digital outputs (24 V DC/0.5 A) - 8 x analogue inputs, 8 x U/I/RTD/TC, 16-bit resolution - 4 x analogue outputs, 4 x U/I, 16-bit resolution - Integrated power supply unit, AC230 V/DC 24 V, 4.5 A - 16 digital inputs and 16 switches/pushbuttons for Signal simulation - 16 digital outputs 4 mm safety sockets - Analogue processing 4 analogue inputs can be switched to simulation via potentiometer and 2 analogue outputs <p>Recommended accessories:</p> <ul style="list-style-type: none"> - I/O data cable - Power cables - Programming software or facility should be included - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			

1.2.11	Ball and Plate Control System			
	<ul style="list-style-type: none"> - Stabilizing a thrown ball onto a plate and it being stabilized exactly in the center within some seconds. - Controlled by NI LabVIEW using a NI interface card <p>Features:</p> <ul style="list-style-type: none"> - Intriguing control experiment featuring extensive courseware - Enables study of real-time control of a non-linear and unstable process - Implementation of digital control techniques using NI LabVIEW - Ball position sensing and image processing using USB camera - Open and closed loop configurations - Fully assembled plant with integral power supply <p>Practical coverage: Non-linear model testing, Plant control PID controllers, Plate orientation control, PID control of plate orientation, Real-time PID control, 1-D Ball Control, 1-D PID control of ball position, Real-time 1-D PID control of ball position, 2-D Ball Control, 2-D PID control of ball position, Real-time 2-D PID control of ball position, Trajectory tracking with ball Real-time.</p> <ul style="list-style-type: none"> - Ball & Plate Control System complete with student software, NI LabVIEW interface card and cable. <p>Specification</p> <ul style="list-style-type: none"> - Power Supply included 230 V AC - A self-contained positional control training instrument utilizing electro-magnetic actuators. - Teaching the principles of position control. - Operates in real-time when connected to a PC via a USB Operates within NI LabVIEW environment. <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.3.1	MIG welding machine			
	<ul style="list-style-type: none"> - DC – Lift inverter multi process welding machine - Should be able to weld the following materials <ul style="list-style-type: none"> - Steel - HSS high strength steel - Stainless steel - MIG – brazing of galvanized sheets - Aluminium - To weld on thin thickness - To modify weld seam during welding <p>Features</p> <ul style="list-style-type: none"> - Visualization on LCD display of welding parameters - Regulation of: wire speed upslope, electronic reactance, 			

	<p>burn-back time and post gas</p> <ul style="list-style-type: none"> - thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator protections <p>Accessories</p> <ul style="list-style-type: none"> - 2 MIG-MAG torches - Spool gun - Cable - Clamp <ul style="list-style-type: none"> - Complete with MIG welding accessories. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.3.2	TIG welding machine			
	<ul style="list-style-type: none"> - TIG, Pulse TIG and MMA inverter welding machine. - Should be able to work in direct current and alternating current. - Should be able to weld the following materials <ul style="list-style-type: none"> - Steel - Stainless steel - Titanium - Copper - Magnesium - Aluminium - Alloys of above materials <p>Characteristics</p> <p>Pulse and EASY pulse operation</p> <ul style="list-style-type: none"> - Adjustable pre-heating for simpler striking in AC - TIG regulations: bi-level, startup/end current, spot welding time, pre/post gas, current up/down slope, balance DC / AC, square wave frequency - THINSPOT function for quick and precise tack welding - MMA regulations: arc force and hot start - Anti-stick device - VRD device - Remote control connector - Thermostatic, overvoltage, undervoltage, overcurrent protections. <ul style="list-style-type: none"> - Complete with TIG welding accessories. - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			

1.3.3	Metallography specimen grinding & polishing machine			
	<ul style="list-style-type: none"> - Metallography specimen preparing for micro structure analysis <p>Main features:</p> <ul style="list-style-type: none"> - Stainless steel parts for rust protection - Double working disks. - Working disk can be changed and replaced swiftly - Step less speed changing status or two-level constant speed status. - Working condition can be switched from one to another easily. - Selection option for rotating direction of working disk <p>Technical specifications:</p> <ul style="list-style-type: none"> - Rotating speed of working disk: 50-600rpm (step less speed changing) - Diameter of working disk: Approximately 300mm - Power supply: 220V 50Hz <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.3.4	Hot Metal Press Machine			
	<p>Metallurgy preparation includes uniform size and shape in order hot mounting (hot compression mounting) is ideal.</p> <ul style="list-style-type: none"> - Operates on electro hydraulic pressure. - HMI LCD display - Quick interchangeable mould cylinders for desired sizes. - Parameters preloaded for quick selection. - Fully automatic - Intermediate ram included for dual mounts - Robust bayonet - Corrosion resistant steel - Cycle completion alarm notification - Temperature up to 300° C - Pressure up to 350 Bars (5000 psi) - Mould Sizes 25mm,30mm,40mm,50mm - Electrical supply: 240V, 1-phase, 50/60 Hz <ul style="list-style-type: none"> - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.3.5	Sheet Metal Arc Welding			
	<p>MMA (Manual Metal Arc) stick electrode welding machine in alternating current (AC).</p> <p>Main Features:</p>			

	<ul style="list-style-type: none"> - Step less regulation of welding current. - Thermostatic protection. - Use with a wide range of electrodes: rutile. - Complete with MMA welding accessories including mask. - Dual voltage power supply. - Fit with accessories and wheels - Step less current adjustment - 230 V single phase , 50/60 Hz - Warranty should be Minimum one year - All relevant technical brochures should be forwarded with Tender Documents. Comprehensive user guide, complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product. Manufactures' authorization should be submitted with the tender documents. 			
1.4.1	MARSHALL STABILITY AND FLOW			
	<p>Load frame</p> <ul style="list-style-type: none"> - Geared screw jack and motor drive - System should have internal limit switch for both directions of travel. - mechanical load frame should be bench mounted and constructed to encompass the Strain and loads involved with the test. - at least 50 kN capacity - Platen speed 50.8 mm per minute - Weight: 65 - 70 kg (total system) - Dimensions (l x w x h): max. 550 x 400 x 870 mm - Power requirements: 220-240 V AC, 50-60 Hz, 1 ph <p>Flow Meter – (02 nos.)</p> <ul style="list-style-type: none"> - Dial gauge graduated 0.01 mm with 25 mm travel. - Supplied with stem brake unit and flow meter pedestal. <p>Breaking Head (Marshall)</p> <ul style="list-style-type: none"> - complete with gauge disc - weight 9 kg <p>Load Measuring Ring 50 kN</p> <ul style="list-style-type: none"> - Should be calibrated in compression <p>Load Measuring Ring 25 kN</p> <ul style="list-style-type: none"> - Should be calibrated in compression <p>Electronic Control and Readout Unit</p> <ul style="list-style-type: none"> - Can be programmed to automatically stop the load frame when transducer limits exceed, protecting test accessories and load frame drive system - To record Peak load and the corresponding flow - software supporting Windows 7 or above to download results - SI Units - Large character LCD display <p>S - type Load Cell</p> <ul style="list-style-type: none"> - 50 kN capacity <p>Flow Transducer</p> <ul style="list-style-type: none"> - Pre-calibrated, for use with Breaking Head 			
	<p>Documentation</p> <p>All relevant technical brochures forwarded with Tender</p>			

	<p>Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum three years</p>			
1.4.2	WATER BATH TO KEEP ASPHALT SPECIMENS BEFORE MARSHALL TEST			
	<ul style="list-style-type: none"> - Capacity - 60 L - LED display - Cover and internal perforated shelf - Temperature range: Ambient to 95°C ± 1°C (controllable) - Power requirements : 220 – 240 V AC, 50 – 60 Hz 1 ph 			
	<p>Documentation</p> <p>All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>			
1.4.3	ASPHALT MIX COMPACTION MOULD AND ACCESSORIES			
	<p>Compaction Mould – 03 Nos.</p> <ul style="list-style-type: none"> - mould body - baseplate - Combined filling/extraction collar - Weight: 3.5 kg <p>Compaction Hammer – 03 Nos.</p> <ul style="list-style-type: none"> - Should satisfy BS 598 - The hammer has a 4535 g sliding weight with a free fall of 457 mm - total Weight: 7.85 kg <p>Compaction Pedestal</p> <ul style="list-style-type: none"> - Should satisfy BS 598 - 300 mm sq x 25 mm thick steel plate complete with 4 tie rods and securing nuts. - A mould clamp and hammer guide are fitted to the plate - Supplied complete with a laminated hardwood block. - Weight 35 - 45 kg <p>Paper Discs (Pack of 100)</p> <ul style="list-style-type: none"> - Non-absorbent, 99 mm diameter <p>Steel Block (To heat the compaction hammer foot)</p> <ul style="list-style-type: none"> - 100 mm diameter x 50 mm height. - Weight max. 3 kg. <p>Spatula (200 mm) – 03 nos.</p>			
	<p>Documentation</p> <p>All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p>			

	<p>After Sales service: Should be available Warranty : Minimum One year</p>			
1.4.4	RING AND BALL APPARATUS AND ACCESSORIES			
	<p>Ring and Ball Apparatus</p> <ul style="list-style-type: none"> - System should be with 2 shouldered pattern rings, 2 ball-centering guides and 2 balls - The support frame of the apparatus should be retained in a heat resistant container - Weight of the system : 550 - 600 g <p>Magnetic stirrer</p> <ul style="list-style-type: none"> - Stirrer should provide fine temperature control of liquid up to a maximum temperature of +150°C. - And should be with variable stirring speed options. - Weight max. 2 kg - Power requirements: 220 – 240 V AC, 50 - 60 Hz, 1 ph <p>Thermometer</p> <ul style="list-style-type: none"> - should offer a thermometer with range suitable for the system 			
	<p>Documentation</p> <p>All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available Warranty : Minimum one year</p>			
1.4.5	PENETRATION TEST AND ACCESSORIES			
	<p>Standard Penetrometer</p> <ul style="list-style-type: none"> - The 150 mm diameter dial should be graduated in 400 divisions of 0.1 mm <p>Semi-automatic Penetrometer</p> <ul style="list-style-type: none"> - Should be incorporated digital Automatic Controller which releases the needle assembly, - The time set should be displayed by a bright, easy to read display. - Weight 8 - 10 kg - Power requirement: 220 – 240 V AC, 50 – 60 Hz, 1 ph. <p>Penetration Needle.</p> <ul style="list-style-type: none"> - Hardened steel, should be supplied with verification certificate - Weight 2.5 g <p>Constant Temperature Bath.</p> <ul style="list-style-type: none"> - A bench mounting bath should be offered specially designed for the conditioning of bitumen samples prior to penetration tests. Must be incorporated with a highly accurate thermostat, the bath should be able to maintain a temperature between 20 and 70°C ± 0.1°C. - Weight 18.2 kg - Power requirements: 220 – 240 V AC, 50 Hz, 1 ph. <p>Transfer Dish should be offered</p> <p>Penetration Tin (For penetrations between 200 and 350) – 03 Nos.</p>			

	<ul style="list-style-type: none"> - Approximately 70 mm diameter x 45 mm deep. - Weight 25 - 35 g <p>Penetration Tin (for penetrations below 200) – 03 Nos.</p> <ul style="list-style-type: none"> - Approximately 55 mm diameter x 35 mm deep. - Weight 20 - 30 g 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>			
1.4.6	DUCTILITY TESTING MACHINE (ELECTRICALLY OPERATED)			
	<ul style="list-style-type: none"> - Must be able to test at least test three specimens simultaneously. - The electric motor driven reduction gear unit must be smooth constant speed on continuous operational conditions. - The system must be mounted with water bath - Completely encased in metal bound hardwood. - The temperature controller must be a digital 88ontroller - Atleast two rates of travel must be provided. - The machine to be supplied complete with 4 ductility molds (Briquette mould), each with a base plate. - Should satisfy ASTM D 113, AASHTO T51standards. 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum two years</p>			
1.5.1	PROCTOR COMPACTION MOULD AND RAMMER			
	<p>Mould</p> <ul style="list-style-type: none"> - Dimensions (dia. X height) : 101.6 x 116.4 mm - Rammer Mould volume : 1/30 ft³ - Construction : All steel, threaded studs with wing nuts, plated - Weight : 5.4 kg <p>Rammer</p> <ul style="list-style-type: none"> - Rammer : 50 mm dia, 2.5 kg - Drop : 300 mm - Guide sleeve : Machined steel tubing with air pressure release holes - Finish : Corrosion resistant - Weight : 4.1 kg <p>Rammer</p> <ul style="list-style-type: none"> - Rammer : 50 mm dia, 4.5 kg - Drop : 450 mm 			

	<ul style="list-style-type: none"> - Guide sleeve : Machined steel tubing with air pressure release holes - Finish : Corrosion resistant - Weight : 7.5 kg <p>Straight edge, 300 mm</p>			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>			
1.5.2	CBR TEST MACHINE			
	<p>Load frame</p> <ul style="list-style-type: none"> - 50 kN load frame complete with stabilising bar. - Must be a two speed machine [covering BS (1.00 mm/min) and ASTM (1.27 mm/min) standards] - Rapid platen adjustment must be available. - Must be a Compact, bench-mounting design. - Options for mechanical or electronic measurement must be available. - Close control of application of a seating load must be available. - Dimensions (l x w x h): 550 x 400 x1220 mm - Maximum vertical clearance : 800 mm - Horizontal clearance : 255 mm - Platen diameter : 133 mm - Platen travel : 105 mm - Weight : 75 - 85 kg - Power requirements: 220 V AC, 50 Hz, 1ph 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum three years</p>			
1.5.3	CBR MOULD AND ACCESSORIES			
	<p>CBR Mould with collar and perforated Baseplate.</p> <ul style="list-style-type: none"> - Mould (inside dia. x height):152 x 127 mm - Collar :51 mm height, fits both ends of mould Base plate: Solid, fits both ends of mould - Construction : All steel, plated - Weight :7.3 kg <p>CBR Perforated Base Plate to fit mould body. CBR Cutting Collar to fit mould body C-spanner to fit CBR moulds and Collars Base Plate Tool to fit into base plate to assist removal from mould body. Static Compaction Plug.</p>			

	<ul style="list-style-type: none"> - Steel, 150 mm dia x 51 mm thick. Complete with removable handle. <p>2 kg Annular Surcharge Weigh</p> <p>2 kg Split Surcharge Weight</p> <p>Tamping Rod</p> <p>Swell Plate with adjustable stem</p> <p>Swell Tripod for mounting Swell Dial Gauge in position on CBR mould collar</p> <p>Soaking Tank</p> <p>Swell Dial Gauge</p> <ul style="list-style-type: none"> - (25 mm travel x 0.01 mm divisions) <p>Filter Papers: Box of 100 Nos</p> <ul style="list-style-type: none"> - 150 mm diameter <p>Penetration Piston</p> <ul style="list-style-type: none"> - 1.935 mm² area foot of case hardened steel. - Weight 3.7 kg. <p>Penetration Dial Gauge</p> <ul style="list-style-type: none"> - 25 mm travel (0.01 mm divisions) - Complete with rack extensions and chisel edge anvil - Weight 220 g <p>Mounting bracket for CBR penetration dial gauges</p> <ul style="list-style-type: none"> - To fix gauges to penetration piston or load ring. 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>			
1.5.4	DYNAMIC CONE PENETROMETER			
	<ul style="list-style-type: none"> - To be supplied with all necessary tools, assembly and operating instructions - Assembled height 1965 mm - Assembled weight 20 kg - an 8 kg weight with a drop of 575 mm, - a 20 mm diameter cone fitted to the end of the shaft - To be used for rapid in-situ measurement of the structural properties of existing road pavement constructed with unbound materials - should be supplied with a Replacement Cone 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>			
1.5.5	CASAGRANDE LIQUID LIMIT DEVICE WITH COUNTER			
	<ul style="list-style-type: none"> - Satisfy BS/EN Standard - Supplied with metal grooving tool & test gauge 			

	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum one year</p>			
1.5.6	LINEAR SHRINKAGE MOULD			
	<ul style="list-style-type: none"> - Satisfy BS 1377 Standard - To produce a specimen 140 mm long x 12.5 mm radius. 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum one year</p>			
1.5.7	SAMPLE EJECTOR			
	<ul style="list-style-type: none"> - Dimensions (w x d x h, inches): max. 10-1/2 x 8 x 22-1/2 - Capacity: 2” and 3” Shelby tubes up to 7”; 4” and 6” molds. - Pushing Force max. 6,000 lbf - Jack Hydraulic; hand-operated; 7” stroke - Construction: All metal; plated extrusion plates and piston discs; painted finish on housing and pump - Weight : 25 – 30 kg - To be supplied with 2” – 6” ejector heads and adapter plates 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product After Sales service: Should be available Warranty : Minimum one year</p>			
1.5.8	Traixal Machine Accessories-CU/CD System (ELE, EL25-4047)			
	<ul style="list-style-type: none"> • De-Aired Water Appartus. 15 L Cap. 220-240V 50/60Hz 1Ph – 01 • Piston Restraint Clamp for Ele Triaxial Cells Manufactured from July 1996 – 1 No • Valve No Volume Change ¼ inch BSp Fitted with 6 mm Connector and Integral Sealing Ring – 1 No • Two –way split former 100 mm diameter – 1No • Porous disc 100mm Diameter Pack of 2 – 1 No • Filter Paper drain 100mm/4 inch diameter. Pack of 50 – 1 No • Pressure test 1700 Oil/Water constant pressure system 0 to 1700Kpa 220-240V 50/60Hz 1Ph. – 2 Nos 			

	<ul style="list-style-type: none"> • Digital Pressure Gauge 1700Kpa for use with 26-1800 series Oil/Water constant pressure system – 1 No • Red dye Kerosene soluble 10G Phial for Colouring Kerosene – 1 No • Digital Pressure Gauge 1700Kpa. For Ele Triaxial Cells. – 1 No 			
	<p>Documentation All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product</p> <p>After Sales service: Should be available</p> <p>Warranty : Minimum one year</p>			
1.5.9	Motorized Pendulum Impact Testing System			
	Impact Energy	300-900 Joule		
	Release Angle (adjustable)	150°		
	Pendulum Length	750 - 770 mm		
	Maximum Hammer Speed	5.0 – 5.5 m/s		
	Encoder Resolution	0.036°		
	System Dimensions(W x D x H)	2200 x 1117 x 1990mm		
	Net Weight	1200 – 1300 kg		
	Power	230 Vac, 1 Phase, 50/60 Hz, 15 Amp		
	Should meet the following standards • ASTM E23 • ISO 148 • EN 10045 • GOST 9454 • AS 1544 • JIS Z 2242 • JIS B 7722			
	Automatic test start at door closure			
	Optional interchangeable hammer weights			
	Safety enclosure with interlocks			
	Data Acquisition Software Specification (English version)			
	Calculations	Energy absorbed and Elasticity/Resilience		
	Data Collection Rate	1 kHz		
	Reporting Capability	Stores results as .csv files that can opened in applications such as Microsoft Excel and Ability to define 10 user-designed input fields		
	Simple System Setup	Hammer characteristics on single setup page and Setup parameters stored to device		
	Display Features	Status of System limits, Hammer setup and verification,		

		Potential/impact energy, velocity and test history and Modulus of Elasticity			
	Package Includes	Angular encoder, USB communication box, Mounting hardware and inter-connect cables and Network connectivity			
	Documentation	All relevant technical brochures forwarded with Tender Documents. Comprehensive user guide, Complete track record on where the supplier has supplied the product, Recommendation letter about the product from the institutions where the supplier has supplied the product			
	Warranty	Minimum three years			
1.5.10	Moisture Can				
	Aluminium, 75x25mm with lids				
1.5.11	Concrete Cube Mould				
	Size - 150x150x150mm, 4-Part Clamp Type / 2-Part (L-Shape) Cast Iron				
1.5.12	Cube Mould Tamping Bar				
	25mm square face, Steel				

Section VII.

Contract Data

The following Contract Data shall supplement and / or amend the Conditions of Contract (CC). Whenever there is a conflict, the provisions herein shall prevail over those in the CC.

CC 1.1(i)	The Purchaser is: University of Jaffna
CC 1.1 (m)	The Project Site(s)/Final Destination(s) is/are: Faculty of engineering, University of Jaffna (Ariviyal Nagar, Kilinochchi premises)
CC 8.1	For notices, the Purchaser's address shall be: Bursar Attention: Bursar Address: University of Jaffna, P.O Box 57, Thirunelvely, Jaffna. Telephone:021-2222644
CC 11	Goods shall be supplies in compliance with the quality and the specification given.
CC 15.1	CC 15.1—The method and conditions of payment to be made to the Supplier under this Contract shall be as follows: A: For Goods offered within Sri Lanka Payment shall be made in Sri Lanka Rupees within thirty (30) days of presentation of claim supported by a certificate from the Purchaser declaring that the Goods have been delivered and that all other contracted Services have been performed. i) On Delivery: up to a maximum of ninety (90) percentage of the Contract Price, shall be paid on receipt of the Goods. ii) On Acceptance: the remaining ten (10) percentage of the Contract Price shall be paid to the Supplier within ninety (90) days. After the certification of acceptance.
CC 17.1	A Performance Security – 10%
CC 26.1	The liquidated damage shall be: 2% per week
CC 26.1	The maximum amount of liquidated damages shall be: 10 %



UNIVERSITY OF JAFFNA
INVITATION FOR BIDS
Supply of Laboratory Equipment & Lab Furniture
to the Faculty of Engineering, University of Jaffna.
UJ/F/PO/T/03/2016

Chairperson, Department Procurement Committee, University of Jaffna, Jaffna, Sri Lanka, invites sealed bids from eligible bidders for supply of following items to the University of Jaffna.

1. Bidding will be conducted through the National Competitive Bidding (NCB) procedure.
2. Bidder should have at least three years experience in the relevant field in Sri Lanka.
3. Interested eligible bidders may obtain further information from the Senior Assistant Bursar / Supplies of the University of Jaffna, and inspect the bidding documents at the Supplies Branch of the University between 9.00 am to 3.00 pm from **23.05.2016 to 22.06.2016**.
4. A complete set of bidding documents in English may be purchased by interested bidders on submission of a written application to the Senior Assistant Bursar / Supplies, University of Jaffna and upon payment of a non-refundable fee of Rupees 2,000/= per package in cash at the Shroff Counter of the University of Jaffna. The bidder can also download the bidding documents from the University website www.jfn.ac.lk. Those who are obtaining bidding documents from the University website should submit the complete documents along with a Bank Draft drawn in favour of the “Bursar, University of Jaffna, Sri Lanka” for Rs. 2,000/= per package as non-refundable fee or the payments could be made to Peoples Bank, Jaffna University Branch, account no: **162-1-001-6-0000880**, and the **cash receipt/deposit slip to be attached with the bidding documents**. The documents may be purchased until 2.30 p.m from **23.05.2016 to 22.06.2016**.
5. Bids must be delivered in duplicate to be addressed **Bursar, University of Jaffna, Thirunelvely**, on or before **2.00p.m on 23.06.2016**. Please indicate the “**Supply of Laboratory Equipment & Lab Furniture - UJ/F/PO/T/03/2016 – 23.06.2016**” on the left hand corner of the envelope.
6. All bids must be accompanied by a Bid Security addressed to the **Chairperson, Department Procurement Committee, University of Jaffna**, valid for 120 days from the date of the bid opening as specified in the following Table.

Serial No	Description Items	Bid Security
Package 01- Mechanical & Civil Engineering Equipment		
01. Mechanical Engineering Equipment(thermodynamics)		
1.1.1	Automotive diesel engine	190,000.00
1.1.2	Gasoline engine	
1.1.3	Free and forced convection apparatus	
1.1.4	Heat conduction and convection apparatus	
1.1.5	Combined convection and radiation	
1.1.6	Universal vibration apparatus	
1.1.7	Universal moulding machine	
1.1.8	Balancing of reciprocating Mass	
1.1.9	Twin Rotor System	
1.1.10	Optical comparator	

2. Mechanical Engineering Equipment (Pneumatic systems)		
1.2.1	Two - stage compressor test set	165,000.00
1.2.2	Multi-pump test rig	
1.2.3	Pelton turbine test rig	
1.2.4	Axial flow turbine test rig	
1.2.5	Free and forced vortex apparatus	
1.2.6	Centrifugal pumps characteristics	
1.2.7	Basic pneumatics training kit	
1.2.8	Basic Electropneumatic Training Kit	
1.2.9	Basic Hydraulics Training Kit	
1.2.10	PLC Trainer Kit	
1.2.11	Ball and Plate Control System	
3. Mechanical Engineering Equipment (Workshop items)		
1.3.1	MIG welding machine	11,000.00
1.3.2	TIG welding machine	
1.3.3	Metallography specimen grinding & polishing machine	
1.3.4	Sheet Metal Arc Welding	
1.3.5	Hot Metal Press Machine	
4. Civil Engineering Equipment (Transportation)		
1.4.1	Marshall Stability And Flow And Accessories	66,000.00
1.4.2	Water Bath To Keep Asphalt Specimens Before Marshall Test	
1.4.3	Asphalt Mix Compaction Mould And Accessories	
1.4.4	Ring And Ball Apparatus And Accessories	
1.4.5	Penetration Test And Accessories	
1.4.6	Ductility Testing Machine (Electrically Operated)	
5. Civil Engineering Equipment (Geotechnical & Concrete)		
1.5.1	Proctor Compaction Mould and Rammer	98,000.00
1.5.2	CBR Test Machine	
1.5.3	CBRMould and Accessories	
1.5.4	Dynamic Cone Penetrometer	
1.5.5	Casagrande Liquid Limit Device with Counter	
1.5.6	Linear Shrinkage Mould	
1.5.7	Sample Ejector	
1.5.8	Triaxial Machines Accessories-Cu/Cd System (ELE,EL25-4047)	
1.5.9	Motorized Pendulum Impact Testing System	
1.5.10	Moisture Can	
1.5.11	Concrete Cube Mould	
1.5.12	Cube Mould Tamping Bar	
Package 02- Lab Furniture		
1. Drafting items furniture		
2.1.1	Drafting table	20,000.00
2.1.2	Drafting board	
2.1.3	Stools for drafting table	
2. Drafting item non furniture		
2.2.1	T square set A2	6,000.00

➤ For Bid Documents & Details visit University website www.jfn.ac.lk

7. Pre Bid meeting will be held on **15th June at 10.00 a.m.** in the Board Room of University of Jaffna
8. The bids shall be deposited in the 'Tender Box' available in the Bursar's Office of the University, or sent under Registered Cover to be received before the deadline to the address given Clause No.5.
9. Late bids will be rejected.
10. The bids will be opened at **2.00p.m on 23.06.2016**, in presence of the bidders or their authorized representatives who choose to attend the bid opening at the board room of the University.

The Chairperson,
Department Procurement Committee,
University of Jaffna,
Jaffna.
TP. / Fax No: 021-2220962, 021-2222644


M. G. L. Maveekumbura
Senior Assistant Bursar (Supplies)
University of Jaffna
Jaffna